

# LP 2,5/12 - Plug

1071723

<https://www.phoenixcontact.com/us/products/1071723>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 12, connection method: Lever Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

## Your advantages

- Large-surface labeling option
- The Push-in technology COMBI plugs for self-assembly provide solutions that users can implement themselves
- Tested for railway applications

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1071723       |
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 10 pc         |
| Sales key                            | BE22          |
| Product key                          | BE2244        |
| GTIN                                 | 4055626761350 |
| Weight per piece (including packing) | 41.77 g       |
| Weight per piece (excluding packing) | 22.22 g       |
| Customs tariff number                | 85366990      |
| Country of origin                    | PL            |

## Technical data

### Notes

|                    |                                                                                                                                                                            |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes on operation | COMBI connectors are connectors without switching capacity in accordance with IEC 61984 and can be connected or disconnected without load or voltage when used as intended |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Product properties

|                     |               |
|---------------------|---------------|
| Product type        | Terminal plug |
| Number of positions | 12            |

#### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                     |      |
|---------------------|------|
| Rated surge voltage | 8 kV |
|---------------------|------|

### Connection data

|                                                                   |                                                       |
|-------------------------------------------------------------------|-------------------------------------------------------|
| Connection method                                                 | Lever Push-in connection                              |
| Stripping length                                                  | 8 mm ... 10 mm                                        |
| Connection in acc. with standard                                  | IEC 60947-7-1                                         |
| Conductor cross-section rigid                                     | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup>            |
| Cross section AWG                                                 | 26 ... 12 (converted acc. to IEC)                     |
| Conductor cross-section flexible                                  | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup>            |
| Conductor cross-section, flexible [AWG]                           | 26 ... 12 (converted acc. to IEC)                     |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>          |
| Flexible conductor cross-section (ferrule with plastic sleeve)    | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>          |
| Nominal current                                                   | 24 A                                                  |
| Maximum load current                                              | 24 A (with 4 mm <sup>2</sup> conductor cross-section) |
| Nominal voltage                                                   | 800 V                                                 |
| Nominal cross section                                             | 2.5 mm <sup>2</sup>                                   |

#### Connection cross sections directly pluggable

|                                                                   |                                             |
|-------------------------------------------------------------------|---------------------------------------------|
| Conductor cross-section rigid                                     | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Conductor cross-section, rigid [AWG]                              | 20 ... 12 (converted acc. to IEC)           |
| Conductor cross-section flexible                                  | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross-section, flexible [AWG]                           | 14 (converted acc. to IEC)                  |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Flexible conductor cross-section (ferrule with plastic sleeve)    | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |

### Dimensions

|        |         |
|--------|---------|
| Width  | 61.8 mm |
| Height | 18.6 mm |
| Depth  | 40.3 mm |

# LP 2,5/12 - Plug

1071723

<https://www.phoenixcontact.com/us/products/1071723>



|        |         |
|--------|---------|
| Length | 18.6 mm |
|--------|---------|

## Material specifications

|                                                                  |                 |
|------------------------------------------------------------------|-----------------|
| Color                                                            | gray (RAL 7042) |
| Flammability rating according to UL 94                           | V0              |
| Insulating material group                                        | I               |
| Insulating material                                              | PA              |
| Static insulating material application in cold                   | -60 °C          |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26           | HL 1 - HL 3     |
| Surface flammability NFPA 130 (ASTM E 162)                       | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)          | passed          |
| Smoke gas toxicity NFPA 130 (SMP 800C)                           | passed          |

## Environmental and real-life conditions

### Ambient conditions

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C (max. operating temperature see derating curve)                    |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (operation)         | 20 % ... 90 %                                                             |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

# LP 2,5/12 - Plug

1071723

<https://www.phoenixcontact.com/us/products/1071723>



## Drawings

### Circuit diagram



# LP 2,5/12 - Plug

1071723

<https://www.phoenixcontact.com/us/products/1071723>



## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1071723>

| <div> <b>cCSAus</b><br/>Approval ID: 80174529</div> |                       |                       |                   |                             |
|--------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                      | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| B                                                                                                                                    |                       |                       |                   |                             |
|                                                                                                                                      | 600 V                 | 20 A                  | 26 - 12           | -                           |
| C                                                                                                                                    |                       |                       |                   |                             |
|                                                                                                                                      | 600 V                 | 20 A                  | 26 - 12           | -                           |
| F                                                                                                                                    |                       |                       |                   |                             |
|                                                                                                                                      | 800 V                 | 20 A                  | 26 - 12           | -                           |
| D                                                                                                                                    |                       |                       |                   |                             |
|                                                                                                                                      | 600 V                 | 5 A                   | 26 - 12           | -                           |

**DNV**  
Approval ID: TAE00004TX

# LP 2,5/12 - Plug

1071723

<https://www.phoenixcontact.com/us/products/1071723>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250306 |
| ECLASS-15.0 | 27250306 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002021 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# LP 2,5/12 - Plug

1071723

<https://www.phoenixcontact.com/us/products/1071723>



## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|                                        | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)