

1439170

https://www.phoenixcontact.com/us/products/1439170

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

SMD female connector, nominal current: 0.5 A, test voltage: 500 V AC, number of positions: 40, pitch: 0.635 mm, color: black, contact surface: Au, contact connection type: Socket, mounting: SMD soldering



Your advantages

- · Design-in support during device development using MCAD/ECAD data and a free sample service
- · Cost and space savings with the comprehensive portfolio available in various stack heights
- · Easy mating with integrated keyways and tolerance compensation for error-free production
- · Absorption of tolerances and mechanical stresses for a secure connection due to the floating function
- · Unique combination: tolerance compensation through floating and very high data transmission possible in one connector

Commercial data

Item number	1439170
Packing unit	500 pc
Minimum order quantity	500 pc
Sales key	AA23
Product key	AAWACG
GTIN	4063151816896
Weight per piece (including packing)	2.182 g
Weight per piece (excluding packing)	2 g
Customs tariff number	85366930
Country of origin	CN



1439170

https://www.phoenixcontact.com/us/products/1439170

Technical data

Product properties

Product type	SMD female connector
Product family	FS 0,635/FV-F- 6,0
Number of positions	40
Pitch	0.635 mm
Number of rows	2
Pin layout	Linear pad geometry

Electrical properties

Properties

Nominal current I _N	0.5 A IEC 60512-5-2:2002-02 (40-pos. / 60-pos. / 80-pos.)
Contact resistance	70 mΩ
Test voltage	500 V AC IEC 60512-4-1:2003-05
Rated voltage (I/1)	125 V
Rated surge voltage (I/1)	0.8 kV

Data transmission

Data transmission rate	40 Gbps
------------------------	---------

Mounting

Mounting type	SMD soldering
Pin layout	Linear pad geometry

Material specifications

Material data - contact

Note	WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material	Cu alloy
Surface characteristics	Selective coating
Metal surface contact area (top layer)	Gold (Au)
Metal surface contact area (middle layer)	Nickel (Ni)
Metal surface soldering area (top layer)	Tin (Sn)
Metal surface soldering area (middle layer)	Nickel (Ni)

Material data - housing

Color (Housing)	black (9005)
Insulating material	LCP
Insulating material group	Illa
CTI according to IEC 60112	175
Flammability rating according to UL 94	V0

Notes



1439170

https://www.phoenixcontact.com/us/products/1439170

Insulating material group

Minimum value for clearance and creepage distance

Notes on operation	The permissible voltage during operation depends on the application, taking into consideration the air clearances and creepage distances within the scope of insulation requirements in accordance with IEC 60664-1.
imensions	
Dimensional drawing	ph ph
Pitch	0.635 mm
Width [w]	23.8 mm
Height [h]	6.5 mm
Length [I]	10.4 mm
Installed height	6 mm
Application	
Contact cover	0.6 mm
Center offset	± 0.7 mm in longitudinal and transverse direction
Stack height	8 mm Tolerance: +0.6 mm (in combination with Range of articles:FS 0,635/MV-R- 5,0)
	11 mm Tolerance: +0.6 mm (in combination with Range of articles:FS 0,635/MV-R- 8,0)
	12 mm Tolerance: +0.6 mm (in combination with Range of articles:FS 0,635/MV-R- 9,0)
Wipe length	0.6 mm
Angular tolerance	± 10 ° in longitudinal and transverse direction (when plugging in)
	± 5 ° in longitudinal and transverse direction (when plugged in)
Axial offset in X direction (longitudinal)	± 0.7 mm (in longitudinal and transverse direction (when plugged in))
Axial offset in Y direction (transversal)	± 0.7 mm (in longitudinal and transverse direction (when plugged in))
lectrical tests	
Thermal test Test group C	
Specification	IEC 60512-5-2:2002-02
Tested number of positions	80
Insulation resistance	
Specification	IEC 60512-3-1:2002-02
	IEC 60512-3-1:2002-02 ≥ 5 GΩ
Insulation resistance, neighboring positions	5 2 071
Air clearances and creepage distances	
Specification	IEC 60664-1:2007-04

IIIa 0.2 mm



1439170

https://www.phoenixcontact.com/us/products/1439170

Environmental and real-life conditions

٠ <i>،</i>		C	1 1
V١	nra	tion	test

Specification	IEC 60068-2-6:2007-12
Frequency	10 - 55 - 10 Hz
Sweep speed	1 octave/min
Amplitude	1.52 mm
Acceleration	181 m/s²
Test duration per axis	2 h
Test directions	X-, Y- and Z-axis

Durability test

Specification	IEC 60512-9-1:2010-03 (following)
Contact resistance R ₁	70 mΩ
Contact resistance R ₂	70 mΩ
Insertion/withdrawal cycles	50
Insulation resistance, neighboring positions	≥ 5 GΩ

Climatic test

Specification	IEC 60068-2-60:2015-06
Corrosive stress	Method 4, 10 days
Thermal stress	125 °C/168 h
Power-frequency withstand voltage	500 V

Ambient conditions

Ambient temperature (operation)	-55 °C 125 °C
Ambient temperature (storage/transport)	-40 °C 70 °C
Relative humidity (storage/transport)	30 % 70 %
Ambient temperature (assembly)	-5 °C 100 °C

Packaging specifications


Dimensional drawing	W. C. A. C.
Type of packaging	44 mm wide tape
[W] tape width	44 mm
[W2] coil overall dimension	≤ 50.4 mm
[A] coil diameter	≤ 330 mm
Outer packaging type	Transparent-Bag



1439170

https://www.phoenixcontact.com/us/products/1439170

Drawings



Type: FS 0,635/...-FV-F-6,0 with FS 0,635/...-FV-F-6,0



1439170

https://www.phoenixcontact.com/us/products/1439170

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1439170

e 911 us	cULus Recognized Approval ID: E118976-20230512				
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
keine					
		29.9 V	0.5 A	-	-



1439170

https://www.phoenixcontact.com/us/products/1439170

Classifications

ECLASS

ECLASS-13.0	27460201	
ECLASS-15.0	27460201	
TIM		

ETIM

ETIM 9.0	EC002637



1439170

https://www.phoenixcontact.com/us/products/1439170

Environmental product compliance

EU RoHS

20 1.01.0	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com