

# SACB-10X0,34/2X0,75-50 PUR - Master cable ring



1517602

<https://www.phoenixcontact.com/us/products/1517602>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Master cable for sensor/actuator boxes, without PE conductor, unshielded, material PUR/PVC, 12-pos., 10 x 0.34 mm<sup>2</sup> and 2 x 0.75 mm<sup>2</sup>, length: 50 m

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1517602       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF45          |
| Product key                          | AF3ZBX        |
| GTIN                                 | 4017918933326 |
| Weight per piece (including packing) | 5,613.2 g     |
| Weight per piece (excluding packing) | 5,476 g       |
| Customs tariff number                | 85444995      |
| Country of origin                    | DE            |

# SACB-10X0,34/2X0,75-50 PUR - Master cable ring



1517602

<https://www.phoenixcontact.com/us/products/1517602>

## Technical data

### Product properties

|                     |                    |
|---------------------|--------------------|
| Product type        | Cable by the meter |
| Application         | Distributor boxes  |
| Number of positions | 12                 |
| LED                 | no                 |


### Electrical properties

|                       |          |
|-----------------------|----------|
| Nominal voltage $U_N$ | 300 V AC |
|                       | 300 V DC |

### Cable/line

|              |      |
|--------------|------|
| Cable length | 50 m |
|--------------|------|

#### PUR/PVC black [PUR]

|                                     |                                                                                           |
|-------------------------------------|-------------------------------------------------------------------------------------------|
| Dimensional drawing                 |       |
| Cable weight                        | 111.1 kg/km                                                                               |
| UL AWM Style                        | 20549                                                                                     |
| Number of positions                 | 12                                                                                        |
| Shielded                            | no                                                                                        |
| Cable type                          | PUR/PVC black [PUR]                                                                       |
| Conductor structure signal line     | 19x 0.15 mm                                                                               |
| AWG signal line                     | 22                                                                                        |
| Conductor structure, voltage supply | 42x 0.15 mm                                                                               |
| AWG power supply                    | 18                                                                                        |
| Conductor cross section             | 10x 0.34 mm <sup>2</sup> (Signal line)<br>2x 0.75 mm <sup>2</sup> (power line)            |
| Wire diameter incl. insulation      | 1.3 mm ±0.1 mm (Signal line)<br>1.8 mm ±0.1 mm (power line)                               |
| External cable diameter             | 8.60 mm ±0.2 mm                                                                           |
| Outer sheath, material              | PUR                                                                                       |
| External sheath, color              | black RAL 9005                                                                            |
| Conductor material                  | Bare Cu litz wires                                                                        |
| Material wire insulation            | PVC                                                                                       |
| Single wire, color                  | brown, blue, white, green, yellow, gray, pink, red, black, violet, white/pink, pink/brown |

# SACB-10X0,34/2X0,75-50 PUR - Master cable ring



1517602

<https://www.phoenixcontact.com/us/products/1517602>

|                                               |                                                                                                   |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------|
| Inner sheath thickness                        | ≥ 0.15 mm                                                                                         |
| Thickness, outer sheath                       | ≥ 0.38 mm                                                                                         |
| Overall twist                                 | Wires twisted in layers                                                                           |
| Nominal voltage, cable                        | 300 V                                                                                             |
| Test voltage                                  | 2000 V                                                                                            |
| Minimum bending radius, fixed installation    | 7.5 x D                                                                                           |
| Minimum bending radius, flexible installation | 10 x D                                                                                            |
| Smallest bending radius, fixed installation   | 65 mm                                                                                             |
| Smallest bending radius, movable installation | 86 mm                                                                                             |
| Dynamic load capacity (bending)               | Max. bending cycles: 1500000, Bending radius: 86 mm, Traversing path: 2 m, Traversing rate: 2 m/s |
| Flame resistance                              | DIN EN 50265                                                                                      |
| Resistance to oil                             | according to VDE 0472 Part 803                                                                    |
| Other resistance                              | Highly resistant to acids, alkaline solutions and solvents                                        |
| Special properties                            | Silicone-free                                                                                     |
| Ambient temperature (operation)               | -40 °C ... 90 °C (cable, fixed installation)                                                      |
|                                               | -5 °C ... 80 °C (Cable, flexible installation)                                                    |
|                                               | 80 °C (in acc. with UL)                                                                           |

# SACB-10X0,34/2X0,75-50 PUR - Master cable ring



1517602

<https://www.phoenixcontact.com/us/products/1517602>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060106 |
| ECLASS-15.0 | 27060106 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC003250 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SACB-10X0,34/2X0,75-50 PUR - Master cable ring



1517602

<https://www.phoenixcontact.com/us/products/1517602>

## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|                                        | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

### EF3.0 Climate Change

|         |                |
|---------|----------------|
| CO2e kg | 19.084 kg CO2e |
|---------|----------------|

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)