

1565706

<https://www.phoenixcontact.com/us/products/1565706>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 4-position, PUR halogen-free, gray RAL 7001, shielded (Advanced Shielding Technology), free cable end, on Socket angled M12, coding: A, cable length: 10 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1565706                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 25 pc                          |
| Note                                 | Made to order (non-returnable) |
| Product key                          | AF1CJA                         |
| GTIN                                 | 4046356315357                  |
| Weight per piece (including packing) | 408.1 g                        |
| Weight per piece (excluding packing) | 381.1 g                        |
| Country of origin                    | PL                             |

# SAC-4P-10,0-100/M12FR SH - Sensor/actuator cable



1565706

<https://www.phoenixcontact.com/us/products/1565706>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Application          | Standard              |
| Number of positions  | 4                     |
| No. of cable outlets | 1                     |
| Shielded             | yes                   |
| Coding               | A                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | HB                                          |
| Seal material                          | NBR                                         |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material for screw connection          | Zinc die-cast, nickel-plated                |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 48 V AC                    |
|                       | 60 V DC                    |
| Nominal current $I_N$ | 4 A                        |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | no |

### Connection data

#### Conductor connection

|                   |                        |
|-------------------|------------------------|
| Tightening torque | 0.4 Nm (M12 connector) |
|-------------------|------------------------|

### Connector

#### Connection 1

# SAC-4P-10,0-100/M12FR SH - Sensor/actuator cable



1565706

<https://www.phoenixcontact.com/us/products/1565706>

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|


## Connection 2

|                     |                   |
|---------------------|-------------------|
| Type                | Socket angled M12 |
| Number of positions | 4                 |
| Coding type         | A                 |

## Cable/line

|              |      |
|--------------|------|
| Cable length | 10 m |
|--------------|------|

## PUR halogen-free gray [280]

|                                 |                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------|
| Dimensional drawing             |  |
| Cable weight                    | 36 kg/km                                                                            |
| UL AWM Style                    | 20549 / 10493 (80°C/300 V)                                                          |
| Number of positions             | 4                                                                                   |
| Shielded                        | yes                                                                                 |
| Cable type                      | PUR halogen-free gray [280]                                                         |
| Conductor structure signal line | 42x 0.10 mm                                                                         |
| AWG signal line                 | 22                                                                                  |
| Conductor cross section         | 4x 0.34 mm² (Signal line)                                                           |
| Wire diameter incl. insulation  | 1.27 mm ±0.02 mm (Signal line)                                                      |
| External cable diameter         | 4.95 mm ±0.2 mm                                                                     |
| Outer sheath, material          | PUR                                                                                 |
| External sheath, color          | gray RAL 7001                                                                       |
| Conductor material              | Bare Cu litz wires                                                                  |
| Material wire insulation        | PP                                                                                  |
| Single wire, color              | brown, white, blue, black                                                           |
| Thickness, insulation           | ≥ 0.21 mm                                                                           |
| Thickness, outer sheath         | approx. 0.50 mm                                                                     |
| Overall twist                   | 4 wires, twisted                                                                    |
| Optical shield covering         | 80 %                                                                                |
| Max. conductor resistance       | max. 58 Ω/km (at 20 °C)                                                             |
| Insulation resistance           | ≥ 100 GΩ*km (at 20 °C)                                                              |
| Wave impedance                  | ≥ 62 Ω (f = 10 MHz)                                                                 |
| Cable capacity                  | ≤ 80 pF/m (Conductor-Conductor)<br>≤ 135 pF/m (Wire/shield)                         |
| Nominal voltage, cable          | ≤ 300 V                                                                             |
| Test voltage                    | ≥ 3000 V                                                                            |

# SAC-4P-10,0-100/M12FR SH - Sensor/actuator cable



1565706

<https://www.phoenixcontact.com/us/products/1565706>

|                                               |                                                                                                                                         |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Minimum bending radius, fixed installation    | 5 x D                                                                                                                                   |
| Minimum bending radius, flexible installation | 10 x D                                                                                                                                  |
| Smallest bending radius, fixed installation   | 25 mm                                                                                                                                   |
| Smallest bending radius, movable installation | 50 mm                                                                                                                                   |
| Dynamic load capacity (bending)               | Max. bending cycles: 10000000, Bending radius: 10 x D, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s <sup>2</sup> |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815                                                                                                |
|                                               | in accordance with DIN EN 50267-2-1                                                                                                     |
| Flame resistance                              | in accordance with UL 758/1581 FT2                                                                                                      |
|                                               | DIN EN 60332-2-2 (20 s)                                                                                                                 |
| Resistance to oil                             | in accordance with DIN EN 60811-2-1                                                                                                     |
| Other resistance                              | Highly resistant to acids, alkaline solutions and solvents                                                                              |
|                                               | hydrolysis and microbe resistant                                                                                                        |
|                                               | Resistant to salt water                                                                                                                 |
|                                               | partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)                                                                            |
|                                               | abrasion-resistant                                                                                                                      |
| Special properties                            | Flexible cable conduit capable                                                                                                          |
|                                               | Silicone-free                                                                                                                           |
|                                               | Free of substances which would hinder coating with paint or varnish                                                                     |
|                                               | Low adhesion surface                                                                                                                    |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)                                                                                            |
|                                               | -25 °C ... 80 °C (Cable, flexible installation)                                                                                         |

## Environmental and real-life conditions

### Ambient conditions


|                                 |                                                |
|---------------------------------|------------------------------------------------|
| Degree of protection            | IP65                                           |
|                                 | IP67                                           |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket)               |
|                                 | -25 °C ... 80 °C (cable, fixed installation)   |
|                                 | -5 °C ... 80 °C (Cable, flexible installation) |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |


## Drawings

Dimensional drawing



M12 x 1 socket, angled, shielded

Schematic diagram




Pin assignment M12 socket, 4-pos., A-coded, view female side

1565706

<https://www.phoenixcontact.com/us/products/1565706>

Diagram




# SAC-4P-10,0-100/M12FR SH - Sensor/actuator cable



1565706

<https://www.phoenixcontact.com/us/products/1565706>

Circuit diagram



Contact assignment of the M12 socket

# SAC-4P-10,0-100/M12FR SH - Sensor/actuator cable



1565706

<https://www.phoenixcontact.com/us/products/1565706>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060311 |
| ECLASS-15.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-4P-10,0-100/M12FR SH - Sensor/actuator cable



1565706

<https://www.phoenixcontact.com/us/products/1565706>

## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|                                        | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)