

# SPE-T1-M8MSM/2,0-99B/M8FSF - Network cable



1150575

<https://www.phoenixcontact.com/us/products/1150575>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Network cable, Single Pair Ethernet CAT B (1 Gbps), 2-position, PUR halogen-free, green, shielded (Advanced Shielding Technology), Plug straight M8-SPE / IP67, on Socket straight M8-SPE / IP67, cable length: 2 m

## Product description

Single Pair Ethernet M8 patch cable

## Your advantages

- Future-proof: standardized connectors in accordance with IEC 63171-5 (IP67)
- Easily integrated: Male and female versions for established inductive sensors and flying leads
- Efficient: Device connectors for SMD, THR, and wave soldering processes enable automated processing
- Straightforward servicing: M8 connectors are compatible with IP20 connectors for SPE
- Safely shielded: patch cables with Advanced Shielding Technology

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1150575                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BF02                           |
| Product key                          | AF1BJI                         |
| GTIN                                 | 4063151148003                  |
| Weight per piece (including packing) | 115.6 g                        |
| Weight per piece (excluding packing) | 115.6 g                        |
| Customs tariff number                | 85444290                       |
| Country of origin                    | PL                             |

1150575

<https://www.phoenixcontact.com/us/products/1150575>

## Technical data

### Product properties

|                      |                         |
|----------------------|-------------------------|
| Product type         | Data cable preassembled |
| Application          | Standard                |
| Sensor type          | Single Pair Ethernet    |
| Number of positions  | 2                       |
| No. of cable outlets | 1                       |
| Shielded             | yes                     |

### Insulation characteristics

|                      |   |
|----------------------|---|
| Overvoltage category | I |
|----------------------|---|

### Interfaces

|                      |                                                    |
|----------------------|----------------------------------------------------|
| Bus system           | Ethernet                                           |
| Signal type/category | Single Pair Ethernet CAT B (ISO/IEC 63171), 1 Gbps |

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | no |

### Electrical properties

|                       |              |
|-----------------------|--------------|
| Nominal voltage $U_N$ | 72 V DC      |
| Transmission medium   | Copper       |
| Transmission speed    | up to 1 Gbps |

### Material specifications

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

### Connection data

#### Connection assignment

|                                                           |                                     |
|-----------------------------------------------------------|-------------------------------------|
| Contact   Color (signal designation)   Contact (optional) | 1 (Plug)   WH (RX/TX+)   1 (Socket) |
|                                                           | 2 (Plug)   BU (RX/TX-)   2 (Socket) |

### Connector


#### Connection 1

# SPE-T1-M8MSM/2,0-99B/M8FSF - Network cable




1150575

<https://www.phoenixcontact.com/us/products/1150575>

|                                        |                                                                                                                                        |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Dimensional drawing                    |  <p>Pin assignment, Single Pair Ethernet, 2 pos.</p> |
| Type                                   | M8 Plug, straight, 2-position, shielded (Advanced Shielding Technology), Keying: SPE                                                   |
| Number of positions                    | 2                                                                                                                                      |
| Shielded                               | yes                                                                                                                                    |
| Shielding                              | Advanced Shielding Technology                                                                                                          |
| Signal type/category                   | Single Pair Ethernet CAT B (IEC 63171)                                                                                                 |
| Insertion/withdrawal cycles            | ≥ 100                                                                                                                                  |
| Insulation resistance                  | ≥ 100 MΩ                                                                                                                               |
| Overvoltage category                   | II                                                                                                                                     |
| Degree of pollution                    | 3                                                                                                                                      |
| Tightening torque                      | 0.2 Nm                                                                                                                                 |
| Material Contact                       | Cu                                                                                                                                     |
| Material Contact surface               | Ni/Au                                                                                                                                  |
| Material Contact carrier               | PP                                                                                                                                     |
| Material Screw connection              | Die-cast zinc, nickel-plated                                                                                                           |
| Material Grip body                     | TPU, hardly inflammable, self-extinguishing                                                                                            |
| Material Seal                          | FKM                                                                                                                                    |
| Flammability rating according to UL 94 | V0                                                                                                                                     |
| Degree of protection                   | IP65<br>IP67                                                                                                                           |
| Ambient temperature (operation)        | -25 °C ... 85 °C                                                                                                                       |
| Standard designation                   | M8 connector                                                                                                                           |
| Standards/regulations                  | IEC 63171-5                                                                                                                            |

## Connection 2

|                     |                                                                                                                                          |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensional drawing |  <p>Pin assignment, Single Pair Ethernet, 2 pos.</p> |
| Type                | M8 Socket, straight, 2-position, shielded (Advanced Shielding                                                                            |

# SPE-T1-M8MSM/2,0-99B/M8FSF - Network cable



1150575


<https://www.phoenixcontact.com/us/products/1150575>

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
|                                        | Technology), Keying: SPE                    |
| Number of positions                    | 2                                           |
| Shielded                               | yes                                         |
| Shielding                              | Advanced Shielding Technology               |
| Signal type/category                   | Single Pair Ethernet CAT B (IEC 63171)      |
| Insertion/withdrawal cycles            | ≥ 100                                       |
| Insulation resistance                  | ≥ 100 MΩ                                    |
| Overvoltage category                   | II                                          |
| Degree of pollution                    | 3                                           |
| Tightening torque                      | 0.2 Nm                                      |
| Material Contact                       | Cu                                          |
| Material Contact surface               | Ni/Au                                       |
| Material Contact carrier               | PP                                          |
| Material Screw connection              | Die-cast zinc, nickel-plated                |
| Material Grip body                     | TPU, hardly inflammable, self-extinguishing |
| Material Seal                          | FKM                                         |
| Flammability rating according to UL 94 | V0                                          |
| Degree of protection                   | IP65                                        |
|                                        | IP67                                        |
| Ambient temperature (operation)        | -25 °C ... 85 °C                            |
| Standard designation                   | M8 connector                                |
| Standards/regulations                  | IEC 63171-5                                 |

## Cable/line

|              |     |
|--------------|-----|
| Cable length | 2 m |
|--------------|-----|

Single Pair Ethernet PUR flexible, green [99B]

|                                |                                                                                      |
|--------------------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing            |  |
| UL AWM Style                   | 20233 (80°C/300 V)                                                                   |
| Number of positions            | 2                                                                                    |
| Shielded                       | yes                                                                                  |
| Cable type                     | Single Pair Ethernet PUR flexible, green [99B]                                       |
| Conductor structure            | 1 x 2 x AWG 22/7, S/FTP                                                              |
| AWG signal line                | 22                                                                                   |
| Conductor cross section        | 2x 0.34 mm²                                                                          |
| Wire diameter incl. insulation | 1.6 mm                                                                               |
| External cable diameter        | 5.50 mm ±0.1 mm                                                                      |

# SPE-T1-M8MSM/2,0-99B/M8FSF - Network cable



1150575

<https://www.phoenixcontact.com/us/products/1150575>

|                                               |                                                        |
|-----------------------------------------------|--------------------------------------------------------|
| Outer sheath, material                        | PUR                                                    |
| External sheath, color                        | green                                                  |
| Conductor material                            | Bare Cu litz wires                                     |
| Material wire insulation                      | Foamed PE                                              |
| Single wire, color                            | white, blue                                            |
| Twisted pairs                                 | 2 cores to the pair                                    |
| Overall twist                                 | 1 pair with fillers twisted horizontally               |
| Optical shield covering                       | 90 %                                                   |
| Insulation resistance                         | $\geq 5 \text{ G}\Omega \cdot \text{km}$               |
| Loop resistance                               | $\leq 120.00 \text{ }\Omega/\text{km}$                 |
| Wave impedance                                | $100 \text{ }\Omega \pm 5 \text{ }\Omega$ (at 100 MHz) |
| Nominal voltage, cable                        | $\leq 100 \text{ V}$                                   |
| Test voltage Core/Core                        | 2000 V (50 Hz, 1 min.)                                 |
| Test voltage Core/Shield                      | 2000.00 V (50 Hz, 1 min.)                              |
| Minimum bending radius, fixed installation    | 4 x D                                                  |
| Minimum bending radius, flexible installation | 8 x D                                                  |
| Smallest bending radius, fixed installation   | 22 mm                                                  |
| Smallest bending radius, movable installation | 44 mm                                                  |
| Halogen-free                                  | according to IEC 60754-1                               |
| Flame resistance                              | according to IEC 60332-1-2                             |
|                                               | UL 1581, Sec. 1061 (Cable Flame)                       |
|                                               | according to CSA FT1                                   |
| Resistance to oil                             | in accordance with DIN EN 60811-404                    |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)           |
|                                               | -25 °C ... 80 °C (Cable, flexible installation)        |
|                                               | -25 °C ... 80 °C (for installation)                    |

## Environmental and real-life conditions

### Ambient conditions

|                      |      |
|----------------------|------|
| Degree of protection | IP65 |
|                      | IP67 |


## Standards and regulations

### M8

|                          |              |
|--------------------------|--------------|
| Standard designation     | M8 connector |
| Standards/specifications | IEC 63171-5  |
| Note                     | T1-SPE       |


## Drawings

Dimensional drawing




M8MSM

Dimensional drawing



M8FSF

Schematic diagram



Pin assignment, Single Pair Ethernet, 2 pos.

# SPE-T1-M8MSM/2,0-99B/M8FSF - Network cable



1150575

<https://www.phoenixcontact.com/us/products/1150575>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060307 |
| ECLASS-15.0 | 27060307 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |
| EF3.0 Climate Change                    |                                          |
| CO2e kg                                 | 10.604 kg CO2e                           |