

SAC-4P-M 8MS/ 1,0-PUR/3P-M 8FS - Sensor/actuator cable

1526350
<https://www.phoenixcontact.com/us/products/1526350>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M8, coding: A, on Socket straight M8, coding: A, cable length: 1 m

Commercial data

Item number	1526350
Packing unit	5 pc
Minimum order quantity	50 pc
Product key	AF1BCA
GTIN	4017918954512
Weight per piece (including packing)	37.8 g
Weight per piece (excluding packing)	37.8 g
Country of origin	PL

SAC-4P-M 8MS/ 1,0-PUR/3P-M 8FS - Sensor/actuator cable



1526350

<https://www.phoenixcontact.com/us/products/1526350>

Technical data

Product properties

Product type	Sensor/actuator cable
Number of positions	3
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated
Outer sheath, material	PUR
Conductor material	Bare Cu litz wires

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A
Max. conductor resistance	78 Ω/km

Mechanical properties

Mechanical data

Max. bending cycles	4000000
---------------------	---------

Signaling

Status display	no
Status display present	no

Connector

Connection 1

Type	Plug straight M8
Number of positions	3

SAC-4P-M 8MS/ 1,0-PUR/3P-M 8FS - Sensor/actuator cable



1526350

<https://www.phoenixcontact.com/us/products/1526350>

Coding type	A
-------------	---

Connection 2

Type	Socket straight M8
Number of positions	3
Coding type	A

Cable/line

Cable length	1 m
--------------	-----

PUR halogen-free black [PUR]

Dimensional drawing		
Cable weight	23 kg/km	
UL AWM Style	20549 / 10493 (80°C/300 V)	
Number of positions	4	
Shielded	no	
Cable type	PUR halogen-free black [PUR]	
Conductor structure signal line	32x 0.10 mm	
AWG signal line	24	
Conductor cross section	4x 0.25 mm ² (Signal line)	
Wire diameter incl. insulation	1.17 mm ±0.02 mm (Signal line)	
External cable diameter	3.95 mm ±0.15 mm	
Outer sheath, material	PUR	
External sheath, color	black-gray RAL 7021	
Conductor material	Bare Cu litz wires	
Material wire insulation	PP	
Single wire, color	brown, white, blue, black	
Thickness, insulation	≥ 0.21 mm (Core insulation)	
	approx. 0.50 mm (Outer cable sheath)	
Overall twist	4 wires, twisted	
Max. conductor resistance	max. 78 Ω/km (at 20 °C)	
Insulation resistance	≥ 100 GΩ*km (at 20 °C)	
Nominal voltage, cable	≤ 300 V	
Test voltage	≥ 3000 V	
Smallest bending radius, fixed installation	20 mm	
Smallest bending radius, movable installation	40 mm	
Dynamic load capacity (bending)	Max. bending cycles: 10000000, Bending radius: 44 mm, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 5	

SAC-4P-M 8MS/ 1,0-PUR/3P-M 8FS - Sensor/actuator cable



1526350

<https://www.phoenixcontact.com/us/products/1526350>

	m/s ²
Dynamic load capacity (torsion)	Torsion: ± 180 °/m, Torsion cycles: ≥ 20000000 , Torsional frequency: 35 cycles/min.
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	in accordance with UL 758/1581 FT2 DIN EN 60332-2-2 (20 s)
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	Highly resistant to acids, alkaline solutions and solvents hydrolysis and microbe resistant partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Special properties	Flexible cable conduit capable Silicone-free Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -25 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 IP67 IP68
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket) -40 °C ... 80 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

SAC-4P-M 8MS/ 1,0-PUR/3P-M 8FS - Sensor/actuator cable

1526350

<https://www.phoenixcontact.com/us/products/1526350>

Drawings

Dimensional drawing



M8 x 1 male plug, straight version

Dimensional drawing



Socket M8 x 1, straight

SAC-4P-M 8MS/ 1,0-PUR/3P-M 8FS - Sensor/actuator cable

1526350

<https://www.phoenixcontact.com/us/products/1526350>

Schematic diagram



Pin assignment M8 plug, 4-pos., view male side

Schematic diagram



Pin assignment M8 socket, 3-pos., view female side

SAC-4P-M 8MS/ 1,0-PUR/3P-M 8FS - Sensor/actuator cable



1526350

<https://www.phoenixcontact.com/us/products/1526350>

Classifications

ECLASS

ECLASS-13.0	27060311
ECLASS-15.0	27060311

ETIM

ETIM 8.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-4P-M 8MS/ 1,0-PUR/3P-M 8FS - Sensor/actuator cable



1526350

<https://www.phoenixcontact.com/us/products/1526350>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	491280f1-6712-451a-b6ee-c250bc22fe80

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com