

RC-17P1N8AC1X7 - Rear panel feed-through



1601566

<https://www.phoenixcontact.com/us/products/1601566>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Rear panel feed-through, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 17, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, Flat gasket, Panel thickness max.: 2.5 mm, cable diameter range: 4.5 mm ... 5.5 mm, coding: N. This product is in the process of being discontinued. This product must no longer be considered for new projects. Please contact your sales representative for alternatives.

Commercial data

Item number	1601566
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB31
Product key	ABRAFJ
GTIN	4046356235426
Weight per piece (including packing)	86.08 g
Weight per piece (excluding packing)	81.72 g
Customs tariff number	85366990
Country of origin	DE

RC-17P1N8AC1X7 - Rear panel feed-through



1601566

<https://www.phoenixcontact.com/us/products/1601566>

Technical data

Notes

Order information:	Order crimp contacts Ø 1 mm separately
--------------------	--

Product properties

Product type	Circular connectors (device side)
--------------	-----------------------------------

Connector

Insulating body

Note	Order information: Order crimp contacts Ø 1 mm separately
Coding	N
Material (Insulating body)	PA 6.6
Connection method	Crimp connection
Contact switching type	Pin
Application	Signal
Number of positions	17
Direction of rotation	Standard
Connection profile	17
Number Contact (Contact group 1)	17
Diameter Contact (Contact group 1)	1 mm
Rated current Contact (Contact group 1)	8 A (for max. connection cross section)
Rated voltage Contact (Contact group 1)	48 V AC 74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

Housing

Type	Feed-through header
Thread type	M23
Design	straight
Type of locking	Screw locking mechanism
Pg screw connection	none
Mounting type	Rear mounting/square flange (4x M3)
Material (Housing)	Metal
Degree of protection (plugged in)	IP67
Seal for the device	Flat gasket

Seal

External cable diameter	4.5 mm ... 5.5 mm
-------------------------	-------------------

Environmental and real-life conditions

RC-17P1N8AC1X7 - Rear panel feed-through



1601566

<https://www.phoenixcontact.com/us/products/1601566>

Ambient conditions

Permissible humidity (storage/transport)
--

50 % ... 65 %


RC-17P1N8AC1X7 - Rear panel feed-through

1601566

<https://www.phoenixcontact.com/us/products/1601566>

Drawings

Schematic diagram



Connector pin assignment

RC-17P1N8AC1X7 - Rear panel feed-through



1601566

<https://www.phoenixcontact.com/us/products/1601566>

Classifications

ECLASS

ECLASS-13.0	27440109
ECLASS-15.0	27440109

ETIM

ETIM 9.0	EC003569
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

RC-17P1N8AC1X7 - Rear panel feed-through



1601566

<https://www.phoenixcontact.com/us/products/1601566>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	6f502d28-88c0-4d19-aaaf-a4063e11fec6

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com