NS 35/ 7,5 UNP AE EP 250X255 - DIN rail, unperforated

3002637

https://www.phoenixcontact.com/us/products/3002637

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

DIN rail, unperforated, Suitable for PxC polyester terminal boxes, material: Steel, galvanized, passivated with a thick layer, color: silver-colored

Your advantages

- The DIN rails should have elongated holes at the front for fixing
- The length of the rails fits the polyester terminal boxes from Phoenix Contact exactly
- Particular attention has been paid to high dimensional accuracy and surface tempering
- The design of the DIN rails corresponds to European standard EN 60715

Commercial data

Item number	3002637
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH91
Product key	BH9Z4X
GTIN	4055626461427
Weight per piece (including packing)	130.4 g
Weight per piece (excluding packing)	130.4 g
Customs tariff number	72166190
Country of origin	DE

NS 35/ 7,5 UNP AE EP 250X255 - DIN rail, unperforated

3002637

https://www.phoenixcontact.com/us/products/3002637

Technical data

Product properties

Product type	DIN rail

Dimensions

Width	35 mm
Height	7.5 mm
Length	243 mm

Material specifications

Color	silver-colored
Material	Steel
Coating	galvanized, passivated with a thick layer

NS 35/ 7,5 UNP AE EP 250X255 - DIN rail, unperforated

3002637

https://www.phoenixcontact.com/us/products/3002637

Classifications

ECLASS

ECLASS-13.0	27400602
ECLASS-15.0	27400602

ETIM

ETIM 9.0	EC001285

UNSPSC

UNSPSC 21.0	39121700

NS 35/ 7,5 UNP AE EP 250X255 - DIN rail, unperforated

3002637

https://www.phoenixcontact.com/us/products/3002637

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%