

UT 4-MTD-R/CVC 690 - Component terminal block



3046238

<https://www.phoenixcontact.com/us/products/3046238>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Component terminal block, nominal current: 32 A

Commercial data

Item number	3046238
Packing unit	50 pc
Minimum order quantity	50 pc
Product key	BE1172
GTIN	4046356625708
Weight per piece (including packing)	11.502 g
Weight per piece (excluding packing)	11.502 g
Country of origin	PL

UT 4-MTD-R/CVC 690 - Component terminal block



3046238

<https://www.phoenixcontact.com/us/products/3046238>

Technical data

Product properties

Product type	Component terminal block
--------------	--------------------------

Electrical properties

Maximum power dissipation for nominal condition	4.06 W
---	--------

Connection data

Nominal current	32 A
-----------------	------

Material specifications

Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Environmental and real-life conditions

Ambient conditions

Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

UT 4-MTD-R/CVC 690 - Component terminal block



3046238

<https://www.phoenixcontact.com/us/products/3046238>

Classifications

ETIM

ETIM 8.0	EC000903
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

UT 4-MTD-R/CVC 690 - Component terminal block



3046238

<https://www.phoenixcontact.com/us/products/3046238>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	cc363f7d-9253-404c-a261-9f333f637f49

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com