

## USB 2.0 Panel Mount Extension Cable (B to Panel Mount B M/F), 1 ft. (0.31 m)

MODEL NUMBER: U025-001-PM



### Highlights

- Add a fixed USB B female port to a custom solution, such as an internally mounted drive
- Data transfer rates (1.5 to 480 Mbps) for low speed and high speed devices
- Premium double-shielded cables with tinned copper braid and aluminum mylar foil feature twisted 28/20 AWG data lines

### System Requirements

- Any device requiring a longer USB cable

### Package Includes

- U025-001-PM 1-ft. (0.31 m) Panel Mount USB 2.0 Extension Cable (USB B M/F)

### Description

This 1-ft. (0.31 m) Panel Mount USB extension cable is manufactured using USB2.0 cable. It features a panel mount connector that allows you to secure a USB B female port in a fixed location, for custom solutions such as an internally mounted drive. It is designed for use with USB 2.0 devices, but is backwards compatible and can also be used with USB 1.1. Made with superior foil shielding for reliable error-free data communications. The cable is manufactured with molded connectors and integral strain relief for extra durability and long life.

### Features

- Add a fixed USB B female port to a custom solution, such as an internally mounted drive
- Data transfer rates (1.5 to 480 Mbps) for low speed and high speed devices
- Premium double-shielded cables with tinned copper braid and aluminum Mylar foil feature twisted 28/20 AWG data lines

## Specifications

OVERVIEW	
UPC Code	037332178473
Technology	USB 2.0 (High Speed)
Cable Type	Passive
CONNECTIONS	
Side A - Connector 1	USB B (MALE)
Side B - Connector 1	USB B (FEMALE) - PANEL MOUNT
Connector Style	Straight
PHYSICAL	



Powering Business Worldwide

TRIPP LITE  
SERIES

Cable Jacket Color	Black
Cable Length (ft.)	1
Cable Length (m)	0.30
Slot or Hole Mount Measurement (Center to Center)	30mm
Shipping Dimensions (hwd / in.)	0.25 x 1.00 x 6.00
Shipping Dimensions (hwd / cm)	0.64 x 2.54 x 15.24
Shipping Weight (lbs.)	0.05
Shipping Weight (kg)	0.02
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	14° to 122°F (-10° to 50°C)
Storage Temperature Range	5° to 140°F (-15° to 60°C)
Operating Humidity Range	0% to 90% RH, Non-Condensing
Storage Humidity Range	0% to 90% RH, Non-Condensing
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	RoHS
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.