SIEMENS

Data sheet US2:52BP3GAXB



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 120V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Black with Clear Lens 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
material of the actuating element	metal mushroom head with plastic lens
type of unlocking device	without
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	black
Holder	
material of the holder	Metal
Contact block/ lampholder	
socket design	BA 9s with LED
number of lampholders	1
Display	
number of LED modules	1
General technical data	
product component	
 lamp transformer 	Yes
• light source	Yes
degree of pollution	1
type of voltage	
 of the operating voltage 	AC
of the input voltage	AC
surge voltage resistance rated value	4 kV
protection class IP	IP66
protection class IP of the terminal	IP20
Weight	0.23 kg
Supply voltage	
type of voltage of the supply voltage of the light source	AC
supply voltage of the light source at AC at 60 Hz rated value	
•	6 V
Inputs/ Outputs	
output voltage 1 of the lamp transformer rated value	6 V
Connections/ Terminals	

type of light source color of the light source White Electrical Safety touch protection against electrical shock Ambient conditions ambient temperature • during operation • during storage LED white finger-safe Finger-safe -35 +70 °C -40 +85 °C		
tightening torque of the screws in the bracket maximum tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in Lamp type of light source color of the light source Electrical Safety touch protection against electrical shock Ambient conditions ambient temperature • during operation • during storage Installation/ mounting/ dimensions shape of the installation opening	type of electrical connection	screw terminal
tightening torque [lbf-in] with screw-type terminals 8 8 lbf-in type of light source color of the light source Electrical Safety touch protection against electrical shock Ambient conditions ambient temperature • during operation -35 +70 °C • during storage Installation/ mounting/ dimensions shape of the installation opening round	 of modules and accessories 	Screw-type terminal
type of light source color of the light source white Electrical Safety touch protection against electrical shock Ambient conditions ambient temperature • during operation • during storage -40 +85 °C Installation/ mounting/ dimensions shape of the installation opening	tightening torque of the screws in the bracket maximum	20 N·m
type of light source color of the light source Electrical Safety touch protection against electrical shock Ambient conditions ambient temperature • during operation • during storage -40 +85 °C Installation/ mounting/ dimensions shape of the installation opening	tightening torque [lbf·in] with screw-type terminals	8 8 lbf-in
color of the light source white Electrical Safety touch protection against electrical shock finger-safe Ambient conditions ambient temperature • during operation • during storage -40 +85 °C Installation/ mounting/ dimensions shape of the installation opening white white ### Comparison ### Comparison	Lamp	
Electrical Safety touch protection against electrical shock Ambient conditions ambient temperature • during operation • during storage -40 +85 °C Installation/ mounting/ dimensions shape of the installation opening round	type of light source	LED
touch protection against electrical shock Ambient conditions ambient temperature • during operation • during storage -40 +85 °C Installation/ mounting/ dimensions shape of the installation opening finger-safe finger-safe -35 +70 °C -40 +85 °C	color of the light source	white
Ambient conditions ambient temperature • during operation • during storage • during storage -40 +85 °C Installation/ mounting/ dimensions shape of the installation opening round	Electrical Safety	
ambient temperature • during operation • during storage • during storage -40 +85 °C Installation/ mounting/ dimensions shape of the installation opening round	touch protection against electrical shock	finger-safe
during operation during storage during storage during storage during storage Installation/ mounting/ dimensions shape of the installation opening round	Ambient conditions	
during storage	ambient temperature	
Installation/ mounting/ dimensions shape of the installation opening round	 during operation 	-35 +70 °C
shape of the installation opening round	during storage	-40 +85 °C
	Installation/ mounting/ dimensions	
Further information	shape of the installation opening	round
	Further information	

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP3GAXB

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP3GAXB

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP3GAXB

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP3GAXB&lang=en

4/8/2024 last modified: