

Selector switch, metal Maintained, short lever 1NO left, 1NO right position , B Cam
3 position Complete device white insert Non-Illuminated UL file E22655 in Vol. 6 (7)
Sec. 13 (2)

| | |
|--|-----------------------------|
| Enclosure | |
| number of command points | 1 |
| delivery state as a kit | No |
| Actuator | |
| material of the actuating element | plastic |
| number of contact modules | 2 |
| type of unlocking device | rotate-to-unlatch mechanism |
| number of switching positions | 3 |
| Front ring | |
| product component front ring | Yes |
| design of the front ring | standard |
| material of the front ring | metal |
| General technical data | |
| product function positive opening | No |
| product component | |
| • light source | No |
| insulation voltage rated value | 600 V |
| protection class IP | IP66 |
| protection class IP of the terminal | IP20 |
| operating frequency maximum | 600 1/h |
| thermal current | 10 A |
| Weight | 0.23 kg |
| Auxiliary circuit | |
| number of NC contacts for auxiliary contacts | 0 |
| number of NO contacts for auxiliary contacts | 2 |
| operational current at AC-15 | |
| • at 110 V rated value | 60 A |
| • at 230 V rated value | 30 A |
| • at 400 V rated value | 15 A |
| • at 500 V rated value | 12 A |
| Connections/ Terminals | |
| type of electrical connection | screw terminal |
| tightening torque of the screws in the bracket maximum | 20 N·m |
| tightening torque [lbf·in] with screw-type terminals | 8 lbf·in |
| Ambient conditions | |
| ambient temperature | |
| • during operation | -35 ... +70 °C |
| • during storage | -40 ... +85 °C |
| Installation/ mounting/ dimensions | |
| shape of the installation opening | round |
| Further information | |

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2BABK2>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2BABK2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2BABK2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2BABK2&lang=en

last modified:

4/8/2024 