

SUPPRESSOR FOR CONTACTORS

RC, 400 VAC/DC, 100 VA

Art.No.: 20012 Weight: 0.028 Country of origin: CZ

Model designation: RC-AD 047/400


400 V AC/DC


For other configurations and voltages, please inquire.

Link to Product

Illustration







Product may differ from Image











Commercial data		
ECLASS-6.0	27371013	
ECLASS-6.1	27371013	
ECLASS-7.0	27371013	
ECLASS-8.0	27371013	

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2025-06-12



stay connected

ECLASS-9.0 27371013 ECLASS-10.1 27371013 ECLASS-11.1 27371013 ECLASS-12.0 27371013 ECLASS-12.0 ECO02488 customs tariff number 85363010 customs tariff number 85363010 EAN 4048879020664 EAN 4048879020664 EAN 4048879020664 Packaging unit 1 Packaging unit 1 Packaging unit 1 Compatibility Compatible with Appropriate contactors universal Electrical data Damping factor 1.5× UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC min. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Material housing Plastic Combatibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Environmental chara		
ECLASS-11.1 27371013 ECLASS-12.0 27371013 ECLASS-12.0 EC002498 customs tariff number 85363010 customs tariff number 85363010 EAN 4048879020664 EAN 4048879020664 EAN 4048879020664 Packaging unit 1 Packaging unit 1 Compatibility Compatible with 1 Appropriate contactors universal Electrical data Damping factor 1.5x UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Environmental	ECLASS-9.0	27371013
ECLASS-12.0 27371013 ETIM-5.0 EC002448 customs tariff number 85363010 customs faiff number 85363010 EAN 4048879020664 EAN 4048879020664 Packaging unit 1 Compatibility Compatible with Appropriate contactors universal Electrical data Damping factor 1.5x UN Holding power max. Input voltage AC min. 1.5x UN Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information Self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Material data Mechanical data Material data Mechanical data Mounting data Height 35 mm <td< td=""><td>ECLASS-10.1</td><td>27371013</td></td<>	ECLASS-10.1	27371013
ETIM-5.0 EC002498	ECLASS-11.1	27371013
customs tariff number 85363010 Customs tariff number 85363010 EAN 40487902064 EAN 404887902064 Packaging unit 1 Packaging unit 1 Compatibility Compatible with Appropriate contactors universal Electrical data Damping factor 1.5× UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Coperating temperature min20 °C	ECLASS-12.0	27371013
customs tariff number 85963010 EAN 4048879020664 EAN 4048879020664 Packaging unit 1 Compatibility Compatible with Appropriate contactors universal Electrical data Damping factor 1.5× UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Input voltage AC max.	ETIM-5.0	EC002498
EAN	customs tariff number	85363010
EAN 4048879020664 Packaging unit 1 Packaging unit 1 Compatibility Compatible with Appropriate contactors universal Electrical data Damping factor 1.5× UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Coperating temperature min20 °C	customs tariff number	85363010
Packaging unit 1 Packaging unit 1 Compatibility Compatible with Appropriate contactors universal Electrical data Damping factor 1.5× UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Environmental characteristics Climatic Environmental characteristics Climatic Operating temperature min20 °C	EAN	4048879020664
Packaging unit 1 Compatibility Compatible with Appropriate contactors universal Electrical data Damping factor 1.5× UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Insultation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Coperating temperature min20 °C		4048879020664
Compatibility Compatible with Appropriate contactors universal Electrical data Damping factor 1.5× UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C		1
Appropriate contactors universal Electrical data Damping factor 1.5× UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Packaging unit	1
Electrical data Damping factor 1.5x UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Wridth 30 mm Depth 18 mm Environmental characteristics Climatic Coperating temperature min20 °C	Compatibility Compatible with	
Damping factor 1.5x UN Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Coperating temperature min20 °C	Appropriate contactors	universal
Holding power max. 100 W Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Coperating temperature min20 °C	Electrical data	
Electrical data Input Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Damping factor	1.5× UN
Input voltage AC min. 250 V Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Holding power max.	100 W
Input voltage AC max. 400 V Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Electrical data Input	
Installation Connection Connection information self-securing cable forks Device protection Media Flame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Input voltage AC min.	250 V
Connection information self-securing cable forks Device protection Media	Input voltage AC max.	400 V
Plame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Installation Connection	
Flame resistance flame retardant Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Connection information	self-securing cable forks
Mechanical data Material data Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Device protection Media	
Material housing Plastic Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Flame resistance	flame retardant
Combustibility class housing (UL94) V-0 Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Mechanical data Material data	
Mechanical data Mounting data Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min. -20 °C	Material housing	Plastic
Height 35 mm Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min. -20 °C	Combustibility class housing (UL94)	V-0
Width 30 mm Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Mechanical data Mounting data	
Depth 18 mm Environmental characteristics Climatic Operating temperature min20 °C	Height	35 mm
Environmental characteristics Climatic Operating temperature min20 °C	Width	30 mm
Operating temperature min20 °C	Depth	18 mm
- Pr	Environmental characteristics Climat	ic
Operating temperature max. 70 °C	Operating temperature min.	-20 °C
	Operating temperature max.	70 °C