

SVS Eco valve plug A-18mm screw terminal

2-pol. + FE, 0,5 - 1,5mm², 8 -10mm, LED+VDR 24V

Art.No.: 7000-29015-0000000

Weight: 0.029

Country of origin: HU

Model designation: MSVSE-EB1X-M20 SVS ECO LED

Form A (18 mm)

24 V AC/DC $\pm 15\%$




LED and VDR


metric

field-wireable

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

[Link to Product](#)**Illustration**



Product may differ from Image



Side 1	
Mounting method	inserted, screwed
Degree of protection (EN IEC 60529)	IP65
Commercial data	
URL Webshop	https://shop.murrelektronik.com/7000-29015-0000000
customs tariff number	85366990
EAN	4048879294478
Packaging unit	1
Electrical data Supply	
Operating voltage AC	24 V
Operating voltage AC min.	20.4 V
Operating voltage AC max.	26.4 V
Operating voltage DC	24 V
Operating voltage DC min.	20.4 V
Operating voltage DC max.	26.4 V
Current operating per contact max.	1.5 A
Diagnostics	
Status indication LED	yellow
Installation	
Connection cross section min.	0.5 mm²
Connection cross section max.	1.5 mm²
Installation Connection	
Tightening torque	0.4 Nm
Tightening torque tolerance	± 0.1 Nm
Tightening torque clamping screw	0.2 Nm
Mounting set	M20 x 1.5
Installation Pin assignment	
No. of poles	PE
Device protection Electrical	
Additional condition protection degree	locked, inserted
Additional suppressor	Varistor

Mechanical data Material data	
Material housing	PA
Color housing	opaque
Material gasket	NBR
Mechanical data Mounting data	
fastening screw	M3
Clamping range min.	8 mm
Clamping range max.	10 mm
Environmental characteristics Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	90 °C
Important installation notes	
Note on bending radius	Attention: Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.
Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.