



Product: 6661PT ☑

Thermostat & Control, #24-2pr, TC, Indiv. Foil, CMP

Product Description

Thermostat & Control Cable, Plenum-CMP, 2-24 AWG solid tinned copper pairs with foam FEP insulation, Individually Beldfoil® shielded and Flamarrest® jacket

Technical Specifications

Product Overview

Suitable Applications:	Thermostat, Control, Noisy Environment

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	2	24 AWG	Solid	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	FEP - Fluorinated Ethylene Propylene (Foam)	0.013 in (0.33 mm)	0.047 in (1.2 mm)	Black & White, Green & Red

Inner Shield

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	24 AWG (Solid) TC

Outer Shield



Outer Jacket

Material	Nom. Thi	ckness	Nom. Diameter
PVDF - Polyvinylidene Fluorio	e 0.015 in (0	.38 mm)	0.155 in
Overall Cable Diameter (Nom	nal):	0.155 ii	n

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Nom. Inductance	Nom. Velocity of Prop.	Max. Current
32.8 Ohm/1000ft	20.8 Ohm/1000ft (68.2 Ohm/km)	34.9 pF/ft (115 pF/m)	62.8 pF/ft (206 pF/m)	60 Ohm	0.21 μH/ft (0.69 μH/m)	53%	1.68 Amps per Conductor at 30°C

Voltage



Mechanical Characteristics

Temperature

UL Temperature Operating

75°C -20°C to +75°C

Stationary Min. Installation Min.

Bend Radius

1.55 in (39.4 mm) 1.55 in		
Max. Pull Tension:	27.1 lbs (12.3 kg)	
Bulk Cable Weight:	16 lbs/1000ft	

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262 (UL 910), FT6
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.476 Revision Date: 09-07-2025

Part Numbers

Variants

Item #	Color	UPC	Footnote
6661PT 0011000	Brown	612825178828	С
ootnote:			C - CF

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.