



**Product:** <u>9622</u> ☑

Electronic, 25 C #16 Str TC, PVC Ins, PVC Jkt

Request Sample

# **Product Description**

Electronic, 25 Conductor 16AWG (19x29) Tinned Copper, PVC Insulation, PVC Outer Jacket

# **Technical Specifications**

## **Product Overview**

Suitable Applications:	Analog Signals & Control (up to 600V); Line Level Audio; Voice Communications; Panel Wiring

## **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	25	16 AWG	19x29	TC - Tinned Copper

#### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PVC - Polyvinyl Chloride	0.031 in (0.79 mm)	0.121 in (3.07 mm)	Black, White, Red, Green, Orange, Blue, White/Black Stripe, Red/Black Stripe, Green/Black Stripe, Orange/Black Stripe, Blue/Black Stripe, Black/White Stripe, Red/White Stripe, Green/White Stripe, Blue/White Stripe, Black/Red Stripe, White/Red Stripe, Orange/Red Stripe, Blue/Red Stripe, Red/Green Stripe, Orange/Green Stripe, Black/White/Red Stripes, White/Black/Red Stripes, Red/Black/White Stripes, Green/Black/White Stripes

## Outer Jacket

Material I	Nom. Thickness Nom. Diameter
PVC - Polyvinyl Chloride (	0.065 in (1.7 mm) 0.879 in (22.3 mm)
erall Cable Diameter (No	Nominal): 0.8

# **Electrical Characteristics**

### Electricals

	Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
I	Conductor(s)	4.4 Ohm/1000ft	19.5 pF/ft (64.0 pF/m)	3.5 Amps per Conductor at 25°C

## Voltage

Voltage Rating 600 V

# **Mechanical Characteristics**

### Temperature



### Bend Radius

Stationary Min. Installation Min. 8.8 in (220 mm) 8.8 in (220 mm)		
Max. Pull Tension:	810 lbs (370 kg)	

Max. Pull Tension:	810 lbs (370 kg)
Bulk Cable Weight:	440 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL 1581 (VW-1), IEC 60332-1-2, VW-1
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

# **History**

Update and Revision:	Revision Number: 0.502 Revision Date: 09-07-2025	

### **Part Numbers**

#### Variants

Item #	Color	UPC	Footnote
9622 060100	Chrome	612825256748	С
9622 0601000	Chrome	612825256755	С
9622 0602000	Chrome	612825256762	
9622 060500	Chrome	612825256779	С

Footnote:	C - CRATE REEL PUT-UP.

#### © 2025 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.