



Catalog No. 9T21S1050

Description: 1A,5kVA,480-120/240,115C,3R,SC8,QMS

UPC No 783173012093

 $\label{tome problem} \mbox{Home} > \mbox{Transformers} > \mbox{Dry Type Vented} > \mbox{Servicenter}$

ABB's Servicenter™ Single-Phase Integral Transformer and load center system comes equipped with an encapsulated transformer wired into rightly sized circuit breakers for both the primary and secondary transformer windings. Qualified to the seismic requirements of IEEE-693-2005 and IBC-2021 and CBC 2022. Accessible mounting flanges with keyhole slotted mounting holes to make installation easy. NEMA 3R painted enclosure. Clear, comprehensive documentation and labeling. The Servicenter system is UL Listed and is suitable for use service equipment with a 10 kAIC short circuit current rating. The load center portion of this system is ready to accept the ABB THQL plug-on circuit breakers.

Descriptors	
Category	Servicenter
Specifications	
TransType	QMS
Phase	1
PriVoltage	480
SecVoltage	120/240
KVA	5.0 KVA
Coil Material	AL
TempRise	115.0 °C
Sub Type	Servicenter (NEMA 3R)
Frequency	60 Hz
TempClass	180.0 °C
AmbTemp	40.0 °C
EnergyEfficiency	None
KFactor	K1
Enclosure Type	NEMA 3R
Classifications	
UL	Yes



Created on: 10/24/2025