



MODEL: CES-32166-18PM-X7

DESCRIPTION: SPEAKER

FEATURES

- enclosed
- holes for panel mounting
- molex connector



SPECIFICATIONS


parameter	conditions/description	min	typ	max	units
input power	max power: 1 minute on, 2 minutes off, 10 cycles		1.0	1.3	W
impedance	at 2.0 kHz, 1.0 W	6.8	8	9.2	Ω
resonant frequency [Fo]	at 1.0 W	1,024	1,280	1,536	Hz
frequency response		Fo		20,000	Hz
sound pressure level	1 W, 10 cm, 2.0 kHz	94	97	100	dB
distortion	at 2.0 kHz, 1.0 W			10	%
buzz, rattle, etc.	must be normal at sine wave between 200 Hz ~ 2 kHz in free air			2.83	V
polarity	cone moves forward w/ positive dc current to "+" terminal				
dimensions	32 x 16 x 6.5				mm
magnet	Nd-Fe-B				
enclosure material	PPA+PC1414				
cone material	PEEK				
terminal	wire leads with connector				
weight			3		g
operating temperature		-20		70	$^{\circ}\text{C}$
storage temperature		-40		85	$^{\circ}\text{C}$
RoHS	yes				
IP level	IPX7				

Notes: 1. All specifications measured at 15~35°C, humidity at 45~85%, under 86~106 kPa pressure, unless otherwise noted.

MECHANICAL DRAWING

units: mm
tolerance: ± 0.5 mm


wire: UL1571 30 AWG
internal speaker: CMS-151135-18SP-X8
connector: Molex 51021-0200
mating connector: Molex 53047-0210



RESPONSE CURVES


Frequency Response Curve

Test Conditions: 1.0 W / 10 cm



Total Harmonic Distortion Curve

Test Conditions: 1.0 W / 10 cm



REVISION HISTORY

rev.	description	date
1.0	initial release	12/05/2023
1.01	CUI Devices rebranded to Same Sky	09/11/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

sameskydevices.com