

12.4 GHz SMA Female Bulkhead Connector Crimp/ Solder Attachment For RG58, .235 inch D Hole

LCCN3153

Configuration

- · SMA Female Connector
- 50 Ohms
- Straight Body Geometry

- RG58 Interface Type
- · Crimp/Solder Attachment
- Bulkhead

Description

The L-com LCCN3153 SMA female connector has a brass body for telecommunications, data communication, general-purpose test, industrial fields, and rack and panel mount applications. This RF connector has a straight body style and beryllium copper contact with gold plating. This threaded standard coaxial connector works on a maximum frequency of 12.4 GHz and provides an excellent maximum VSWR of 1.3.

The 12.4 GHz SMA connector is available in a 0.760-inch length, 0.315-inch width, and 0.315-inch height. This straight coaxial connector has bulkhead mount with 0.235 hole spacing. The RG58 coax connector allows developers to configure and customize their signal connections however they desire. This SMA connector with crimp/solder attachment has a high-quality construction and an impedance of 50 ohms.

The LCCN3153 RG58 coax RF connector with bulkhead mount has nickel body plating. This 12.4 GHz brass coaxial connector comes with PTFE insulation. The SMA female connector weighs 0.01 pounds and is most used in USB software-defined radio dongles, handheld radios, mobile phone antennas, Wi-Fi antenna systems, and microwave systems.

L-com has the largest in-stock selection of RF and coaxial connectors with same-day shipping for domestic and international orders. We currently have a variety of antenna, audio/video, Ethernet, fiber optic, and USB connectors in our portfolio that are ready to ship today. For further information on similar products, our expert technical support and knowledgeable sales team can help you get the high-quality RF connector that meets your requirements.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
VSWR			1.3:1	
Operating Voltage (AC)			500	Vrms

Mechanical Specifications

Size

Length	0.76in	[19.3mm]
Width/Dia. Height	0.315in 0.315in	[8.00mm] [8mm]
Weight	0.01lbs	[4.54g]

Material Specifications

Description Material Platin

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 12.4 GHz SMA Female Bulkhead Connector Crimp/Solder Attachment For RG58, .235 inch D Hole LCCN3153



12.4 GHz SMA Female Bulkhead Connector Crimp/ Solder Attachment For RG58, .235 inch D Hole

LCCN3153

Contact	Beryllium Copper	Gold
		50 μin minimum
nsulation	PTFE	
Body	Brass	Nickel
		100 µin minimum
Crimp Sleeve	Brass	Nickel
Nasher	Brass	Nickel

Environmental Specifications

Compliance Certifications (see product page for current document)

Plotted and Other Data

12.4 GHz SMA Female Bulkhead Connector Crimp/Solder Attachment For RG58, .235 inch D Hole from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 12.4 GHz SMA Female Bulkhead Connector Crimp/Solder Attachment For RG58, .235 inch D Hole LCCN3153

URL: https://www.l-com.com/12.4-ghz-sma-female-bulkhead-connector-crimp-solder-attachment-rg58-.235-inch-d-hole-lccn3153-p. aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

