

## SMA Male to 1.85mm Male Cable 200 CM Length Using FM-103FLEX Coax

The SMA male to 1.85mm male 200 cm cable using FM-103FLEX coax, part number FMCA1973-200CM, from Fairview Microwave is in-stock and ships same day. This Fairview SMA to 1.85mm cable assembly has a male to male gender configuration with 50 ohm flexible FM-103FLEX coax. Fairview Microwave's flexible RF cable assemblies are ideal for applications where tight bends and continual flexure are required. The FMCA1973-200CM SMA male to 1.85mm male cable assembly operates to 26.5 GHz. The triple shielding of this Fairview cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

### Electrical Specifications

| Description             | Min | Typ         | Max   | Units        |
|-------------------------|-----|-------------|-------|--------------|
| Frequency Range         | DC  |             | 26.5  | GHz          |
| VSWR                    |     |             | 1.4:1 |              |
| Velocity of Propagation |     | 76          |       | %            |
| RF Shielding            | 90  |             |       | dB           |
| Capacitance             |     | 26 [85.3]   |       | pF/ft [pF/m] |
| Inductance              |     | 65 [213.25] |       | uH/ft [uH/m] |
| Input Power (Peak)      |     |             | 550   | Watts        |

### Performance by Frequency

| Description           | F1   | F2   | F3   | F4   | F5    | Units |
|-----------------------|------|------|------|------|-------|-------|
| Frequency             | 1    | 2    | 4.5  | 9    | 26.5  | GHz   |
| Insertion Loss (Max.) | 2.01 | 2.71 | 4.1  | 5.85 | 10.56 | dB    |
| Insertion Loss (Typ.) | 1.85 | 2.48 | 3.75 | 5.34 | 9.62  | dB    |

### Mechanical Specifications

#### Cable Assembly

|          |                   |
|----------|-------------------|
| Length*  | 78.74 in [200 cm] |
| Diameter | 0.35 in [8.89 mm] |

#### Cable

|                                      |                      |
|--------------------------------------|----------------------|
| Cable Type                           | FM-103FLEX           |
| Impedance                            | 50 Ohms              |
| Inner Conductor Type                 | Stranded             |
| Inner Conductor Material and Plating | Copper, Silver       |
| Dielectric Type                      | PTFE                 |
| Number of Shields                    | 3                    |
| Shield Layer 1                       | Silver Plated Copper |
| Shield Layer 2                       | Conductive Tape      |



### Configuration:

- SMA Male
- 1.85mm Male
- FM-103FLEX

### Features:

- Max Frequency 26.5 GHz
- Shielding Effectivity > 90 dB
- 76% Phase Velocity
- Triple Shielded
- ETFE Jacket

### Applications:

- General Purpose
- Laboratory Use

Fairview Microwave  
 301 Leora Ln., Suite 100  
 Lewisville, TX 75056  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

|                 |                      |
|-----------------|----------------------|
| Shield Layer 3  | Silver Plated Copper |
| Jacket Material | ETFE, Gray           |
| Jacket Diameter | 0.103 in [2.62 mm]   |

|                              |                    |
|------------------------------|--------------------|
| One Time Minimum Bend Radius | 0.32 in [8.13 mm]  |
| Repeated Minimum Bend Radius | 0.96 in [24.38 mm] |
| Typical Flex Cycles          | 500,000            |

### Connectors

| Description                     | Connector 1                                     | Connector 2                |
|---------------------------------|-------------------------------------------------|----------------------------|
| Type                            | SMA Male                                        | 1.85mm Male                |
| Impedance                       | 50 Ohms                                         | 50 Ohms                    |
| Contact Material & Plating      | Beryllium Copper, Gold                          | Beryllium Copper, Gold     |
| Contact Plating Spec.           | ASTM-B488 50µ In. Min ASTM-B488 50µ In. Minimum |                            |
| Dielectric Type                 | PTFE                                            | PPO                        |
| Body Material & Plating         | Passivated Stainless Steel                      | Passivated Stainless Steel |
| Body Plating Spec.              | SAE-AMS-2700                                    | SAE-AMS-2700               |
| Coupling Nut Material & Plating | Passivated Stainless Steel                      | Passivated Stainless Steel |
| Coupling Nut Plating Spec.      | SAE-AMS-2700                                    | SAE-AMS-2700               |
| Hex Size                        | 5/16 Inch                                       | 5/16 Inch                  |
| Torque                          | 8 in-lbs 0.9 Nm                                 | 8 in-lbs 0.9 Nm            |

### Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8"$ , whichever is greater.

### Environmental Specifications

#### Temperature

Operating Range -45 to +125 deg C

### Compliance Certifications (see [product page](#) for current document)

### Plotted and Other Data

#### Notes:

- Values at 25°C, sea level.

### How to Order

Part Number Configuration:

**FMCA1973 - xx uu**

\_\_\_\_\_ cm = Centimeters  
 \_\_\_\_\_ <blank> = Inches  
 \_\_\_\_\_ Length


Example: FMCA1973-12 = 12 inches long cable  
 FMCA1973-100cm = 100 cm long cable

SMA Male to 1.85mm Male Cable 200 CM Length Using FM-103FLEX Coax from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link to obtain additional part information: [SMA Male to 1.85mm Male Cable 200 CM Length Using FM-103FLEX Coax FMCA1973-200CM](https://www.fairviewmicrowave.com/sma-male-1.85mm-male-FM-103FLEX-cable-assembly-FMCA1973-200cm-p.aspx)

URL: <https://www.fairviewmicrowave.com/sma-male-1.85mm-male-FM-103FLEX-cable-assembly-FMCA1973-200cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



| REVISIONS |                 |          |          |
|-----------|-----------------|----------|----------|
| REV.      | DESCRIPTION     | DATE     | APPROVED |
| A         | INITIAL RELEASE | 11/08/19 | S.ELLIS  |



FM LABEL:

www.FAIRVIEWMICROWAVE.com  
FMCA1973

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

|                                                                                           |           |                                                                                                                    |             |                                                                                                                                                                                                                                                              |  |
|-------------------------------------------------------------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <p><b>Fairview Microwave</b><br/>an INFINITE brand</p>                                    |           | <p>UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES<br/>DIMENSIONS IN [ ] ARE MILLIMETERS</p>              |             | <p>THIRD-ANGLE PROJECTION</p>                                                                                                                                                                                                                                |  |
| <p>TITLE</p> <p>SMA Male to 1.85mm Male Cable 200 CM Length<br/>Using FM-103FLEX Coax</p> |           | <p>TOLERANCES:</p> <p>.X = ±.2 [5.08] FRACTIONS ± 1/32<br/>.XX = ±.02 [.51] ANGLES ± 1°<br/>.XXX = ±.005 [.13]</p> |             | <p>CABLE LENGTH (L) TOLERANCES:</p> <p>L ≤ 12 [305] = +1 [25] / -0<br/>12 [305] &lt; L ≤ 60 [1524] = +2 [51] / -0<br/>60 [1524] &lt; L ≤ 120 [3048] = +4 [102] / -0<br/>120 [3048] &lt; L ≤ 300 [7620] = +6 [152] / -0<br/>300 [7620] &lt; L = +5%L / -0</p> |  |
| <p>ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.</p>                                       |           | <p>SCALE</p> <p>N/A</p>                                                                                            |             | <p>SHEET 1 OF 1</p>                                                                                                                                                                                                                                          |  |
| SIZE                                                                                      | CAGE CODE | DRAWN BY                                                                                                           | PART NUMBER | REV                                                                                                                                                                                                                                                          |  |
| A                                                                                         | 3FKR5     | K.DANG                                                                                                             | FMCA1973    | A                                                                                                                                                                                                                                                            |  |

T-Rev.D