TRENCHSTOP™ Advanced Isolation

TRENCHSTOP™ IGBT copacked with Rapid 1 fast and soft antiparallel diode in fully isolated package





Fully isolated package TO-247

Features:

TRENCHSTOP™ technology offers :
- Very low $V_{CE(sat)}$
- Short circuit withstand time 5µs at T_{vj} = 175°C
- Positive temperature coefficient in $V_{CE(sat)}$
- Low EMI
- Very soft, fast recovery anti-parallel diode
- Maximum junction temperature 175°C
- 2500 V_{RMS} electrical isolation, 50/60 Hz, t = 1 min
- 100 % tested isolated mounting surface
- Pb-free lead plating; RoHS compliant
- Complete product spectrum and PSpice Models :

http://www.infineon.com/igbt

Potential Applications:

- General Purpose Drives (GPD)
- Servo Drives
- Industrial UPS
- Welding
- Solar String Inverter

Product Validation:

Qualified for industrial applications according to the relevant tests of JEDEC 47/20/22

Key Performance and Package Parameters

Type	V_{CE}	I_C	V_{CEsat}, T_{vj}=25°C	T_{vjmax}	Marking	Package
IKFW75N60ET	600V	75A	1.5V	175°C	K75DET	PG-TO247-3-AI

Table of Contents

Description 1
Table of Contents 2
Maximum Ratings 3
Thermal Resistance 3
Electrical Characteristics 4
Electrical Characteristics Diagrams 6
Package Drawing 13
Testing Conditions 14
Revision History 15
Disclaimer 16

Maximum Ratings

For optimum lifetime and reliability, Infineon recommends operating conditions that do not exceed 80% of the maximum ratings stated in this datasheet.

Parameter	Symbol	Value	Unit
Collector-emitter voltage, $T_{vj} \geq 25°C$	V_{CE}	600	V
DC collector current, limited by T_{vjmax} $T_h = 25°C$ $T_h = 65°C$ $T_h = 65°C$	I_C	80.0 72.0 95.0[1)]	A
Pulsed collector current, t_p limited by T_{vjmax}	I_{Cpuls}	225.0	A
Turn off safe operating area $V_{CE} \leq 600V$, $T_{vj} \leq 175°C$, $t_p = 1µs$	-	225.0	A
Diode forward current, limited by T_{vjmax} $T_h = 25°C$ value limited by bondwire $T_h = 65°C$	I_F	80.0 72.0	A
Diode pulsed current, t_p limited by T_{vjmax}	I_{Fpuls}	225.0	A
Gate-emitter voltage Transient Gate-emitter voltage ($t_p \leq 10µs$, $D < 0.010$)	V_{GE}	±20 ±30	V
Short circuit withstand time $V_{GE} = 15.0V$, $V_{CC} \leq 400V$ Allowed number of short circuits < 1000 Time between short circuits: ≥ 1.0s $T_{vj} = 150°C$	t_{SC}	5	µs
Power dissipation $T_h = 25°C$ Power dissipation $T_h = 65°C$	P_{tot}	178.0 130.0	W
Operating junction temperature	T_{vj}	-40...+175	°C
Storage temperature	T_{stg}	-55...+150	°C
Soldering temperature, wave soldering 1.6mm (0.063in.) from case for 10s		260	°C
Mounting torque, M3 screw Maximum of mounting processes: 3	M	0.6	Nm
Isolation voltage RMS, f = 50/60Hz, t = 1min[2)]	V_{isol}	2500	V

Thermal Resistance

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
R_{th} Characteristics						
IGBT thermal resistance,[3)] junction - heatsink	$R_{th(j-h)}$		-	0.71	0.84	K/W
Diode thermal resistance,[3)] junction - heatsink	$R_{th(j-h)}$		-	1.00	1.10	K/W
Thermal resistance junction - ambient	$R_{th(j-a)}$		-	-	65	K/W

[1)] Equivalent current rating in TO-247-3 at $T_h = 65°C$ using reference insulation material: 152µm, 1.3 W/mK, standard polyimide based reinforced carrier insulator
[2)] For a proper handling and assembly of the advanced isolation device in the application refer to the note at the package drawing.
[3)] At force on body F = 500N, $T_a = 25°C$

Electrical Characteristic, at T_{vj} = 25°C, unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
Static Characteristic						
Collector-emitter breakdown voltage	$V_{(BR)CES}$	V_{GE} = 0V, I_C = 0.50mA	600	-	-	V
Collector-emitter saturation voltage	V_{CEsat}	V_{GE} = 15.0V, I_C = 75.0A T_{vj} = 25°C T_{vj} = 175°C	- -	1.50 1.90	2.00 -	V
Diode forward voltage	V_F	V_{GE} = 0V, I_F = 75.0A T_{vj} = 25°C T_{vj} = 175°C	- -	1.45 1.40	1.75 -	V
Gate-emitter threshold voltage	$V_{GE(th)}$	I_C = 1.20mA, V_{CE} = V_{GE}	4.1	4.9	5.7	V
Zero gate voltage collector current	I_{CES}	V_{CE} = 600V, V_{GE} = 0V T_{vj} = 25°C T_{vj} = 175°C	- -	- 1200	40 -	µA
Gate-emitter leakage current	I_{GES}	V_{CE} = 0V, V_{GE} = 20V	-	-	100	nA
Transconductance	g_{fs}	V_{CE} = 20V, I_C = 75.0A	-	34.0	-	S

Electrical Characteristic, at T_{vj} = 25°C, unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
Dynamic Characteristic						
Input capacitance	C_{ies}	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz	-	4726	-	pF
Output capacitance	C_{oes}		-	215	-	
Reverse transfer capacitance	C_{res}		-	127	-	
Gate charge	Q_G	V_{CC} = 480V, I_C = 50.0A, V_{GE} = 15V	-	440.0	-	nC
Internal emitter inductance measured 5mm (0.197 in.) from case	L_E		-	13.0	-	nH
Short circuit collector current Max. 1000 short circuits Time between short circuits: ≥ 1.0s	$I_{C(SC)}$	V_{GE} = 15.0V, V_{CC} ≤ 400V, t_{SC} ≤ 5µs T_{vj} = 150°C	-	690	-	A

Switching Characteristic, Inductive Load

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
IGBT Characteristic, at T_{vj} = 25°C						
Turn-on delay time	$t_{d(on)}$	T_{vj} = 25°C, V_{CC} = 400V, I_C = 75.0A, V_{GE} = 0.0/15.0V, $R_{G(on)}$ = 5.0Ω, $R_{G(off)}$ = 5.0Ω, $L\sigma$ = 75nH, $C\sigma$ = 30pF $L\sigma$, $C\sigma$ from Fig. E Energy losses include "tail" and diode reverse recovery.	-	33	-	ns
Rise time	t_r		-	45	-	ns
Turn-off delay time	$t_{d(off)}$		-	340	-	ns
Fall time	t_f		-	35	-	ns
Turn-on energy	E_{on}		-	2.70	-	mJ
Turn-off energy	E_{off}		-	2.35	-	mJ
Total switching energy	E_{ts}		-	5.05	-	mJ

Diode Characteristic, at T_{vj} = 25°C

Diode reverse recovery time	t_{rr}	T_{vj} = 25°C, V_R = 400V, I_F = 75.0A, di_F/dt = 1000A/µs	-	107	-	ns
Diode reverse recovery charge	Q_{rr}		-	1.94	-	µC
Diode peak reverse recovery current	I_{rrm}		-	23.0	-	A
Diode peak rate of fall of reverse recovery current during t_b	di_{rr}/dt		-	-1687	-	A/µs

Switching Characteristic, Inductive Load

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
IGBT Characteristic, at T_{vj} = 175°C						
Turn-on delay time	$t_{d(on)}$	T_{vj} = 175°C, V_{CC} = 400V, I_C = 75.0A, V_{GE} = 0.0/15.0V, $R_{G(on)}$ = 5.0Ω, $R_{G(off)}$ = 5.0Ω, $L\sigma$ = 75nH, $C\sigma$ = 30pF $L\sigma$, $C\sigma$ from Fig. E Energy losses include “tail” and diode reverse recovery.	-	32	-	ns
Rise time	t_r		-	47	-	ns
Turn-off delay time	$t_{d(off)}$		-	377	-	ns
Fall time	t_f		-	40	-	ns
Turn-on energy	E_{on}		-	3.96	-	mJ
Turn-off energy	E_{off}		-	3.12	-	mJ
Total switching energy	E_{ts}		-	7.08	-	mJ

Diode Characteristic, at T_{vj} = 175°C

Diode reverse recovery time	t_{rr}	T_{vj} = 175°C, V_R = 400V, I_F = 75.0A, di_F/dt = 1000A/µs	-	170	-	ns
Diode reverse recovery charge	Q_{rr}		-	4.93	-	µC
Diode peak reverse recovery current	I_{rrm}		-	39.0	-	A
Diode peak rate of fall of reverse recovery current during t_b	di_{rr}/dt		-	-1704	-	A/µs



Figure 1. **Forward bias safe operating area**
(D=0, T_h=25°C, T_j≤175°C, V_{GE}=15V, t_p≤1µs)



Figure 2. **Power dissipation as a function of heatsink temperature**
(T_j≤175°C)



Figure 3. **Collector current as a function of heatsink temperature**
(V_{GE}≥15V, T_j≤175°C, insulator film: 152µm, 1.3W/mK)



Figure 4. **Typical output characteristic**
(T_j=25°C)



Figure 5. **Typical output characteristic**
(T_j=175°C)



Figure 6. **Typical transfer characteristic**
(V_{CE}=20V)



Figure 7. **Typical collector-emitter saturation voltage as a function of junction temperature**
(V_{GE}=15V)



Figure 8. **Typical switching times as a function of collector current**
(ind. load, T_j=175°C, V_{CE}=400V, V_{GE}=0/15V, R_G=5Ω, test circuit in Fig. E)



Figure 9. **Typical switching times as a function of gate resistor**
(ind. load, T_j=175°C, V_{CE}=400V, V_{GE}=0/15V, I_C=75A, test circuit in Fig. E)



Figure 10. **Typical switching times as a function of junction temperature**
(ind. load, V_{CE}=400V, V_{GE}=0/15V, I_C=75A, r_G=5Ω, test circuit in Fig. E)



Figure 11. **Gate-emitter threshold voltage as a function of junction temperature**
(I_C=1.2mA)



Figure 12. **Typical switching energy losses as a function of collector current**
(ind. load, T_j=175°C, V_{CE}=400V, V_{GE}=0/15V, R_G=5Ω, test circuit in Fig. E)



Figure 13. **Typical switching energy losses as a function of gate resistor**
(ind. load, T_j=175°C, V_{CE}=400V, V_{GE}=0/15V, I_C=75A, test circuit in Fig. E)



Figure 14. **Typical switching energy losses as a function of junction temperature**
(ind load, V_{CE}=400V, V_{GE}=0/15V, I_C=75A, R_G=5Ω, test circuit in Fig. E)



Figure 15. **Typical switching energy losses as a function of collector emitter voltage**
(ind. load, T_j=175°C, V_{GE}=0/15V, I_C=75A, R_G=5Ω, test circuit in Fig. E)



Figure 16. **Typical gate charge**
(I_C=75A)



Figure 17. **Typical capacitance as a function of collector-emitter voltage** (V_{GE}=0V, f=1MHz)



Figure 18. **Typical short circuit collector current as a function of gate-emitter voltage** (V_{CE}≤400V, start at T_j=25°C)



Figure 19. **Short circuit withstand time as a function of gate-emitter voltage** (V_{CE}≤400V, start at T_j≤150°C)



Figure 20. **IGBT transient thermal impedance as a function of pulse width** (D=t_p/T)



Figure 21. **Diode transient thermal impedance as a function of pulse width** ($D=t_p/T$)



Figure 22. **Typical reverse recovery time as a function of diode current slope** (V_R=400V)



Figure 23. **Typical reverse recovery charge as a function of diode current slope** (V_R=400V)



Figure 24. **Typical reverse recovery current as a function of diode current slope** (V_R=400V)



Figure 25. **Typical diode peak rate of fall of reverse recovery current as a function of diode current slope**
(V_R=400V)



Figure 26. **Typical diode forward current as a function of forward voltage**



Figure 27. **Typical diode forward voltage as a function of junction temperature**

PG-TO247-3-AI (PG-HSIP247-3)



NOTES:
1) ABOVE ISOLATION LAYER DIMENSION IS UNDER NON-FORCE APPLIED CONDITION
2) MOLD GATE PROTRUSION AFTER DEGATING
ALL METAL SURFACES TIN PLATED EXCEPT AREA OF CUT

DIMENSIONS	MILLIMETERS	
	MIN.	MAX.
A	-	5.18
A1	4.70	4.90
A2	2.23	2.59
A3	0.20	0.28
b	1.10	1.30
c	0.50	0.70
D	22.20	22.40
D1	16.96	17.16
E	15.70	15.90
E1	13.68	13.88
e	5.44	
L	18.31	18.91
L1	2.76	2.96
øP	3.50	3.70
øP1	5.70	5.90
Q	5.96	6.36

DOCUMENT NO. Z8B00186434
REVISION 02
SCALE 3:1 0 1 2 3 4 5 6 7 8mm
EUROPEAN PROJECTION
ISSUE DATE 05.06.2018

Note: For a proper handling and assembly of the advanced isolation device in the application the isolation layer must not be exposed to potential penetration via sharp implements or mechanical impacts/shocks, which exceed levels indicated in International Standard (IEC60068-2-6 and IEC60068-2-27). The advanced isolation device is intended only to be used assembled on an appropriate heatsink with recommended flatness of <20µm per 100mm and roughness of <10µm.

Testing Conditions



Figure A. **Definition of switching times**



Figure B. **Definition of switching losses**



Figure C. **Definition of diode switching characteristics**



Figure D. **Thermal equivalent circuit**



Figure E. **Dynamic test circuit**
Parasitic inductance L_σ,
parasitic capacitor C_σ,
relief capacitor C_r,
(only for ZVT switching)

Revision History

IKFW75N60ET

Revision: 2017-09-21, Rev. 2.1

Previous Revision

Revision	Date	Subjects (major changes since last revision)
2.1	2017-09-21	Final data sheet

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Published by
Infineon Technologies AG
81726 München, Germany
© Infineon Technologies AG 2018.
All Rights Reserved.

Important Notice
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (www.infineon.com).

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.

Warnings
Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.