








Jan.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- Notes 1. Lead coplanarity to be 0.1 max.
2. All dimensions without tolerance are dimensions for reference.
3. Package : 1000PCS/Reel

2	PHOSPHOR BRONZE	CONTACT AREA : GOLD 0.2μm MIN.	5	PET	(TOP COVER TAPE)				
		LEAD AREA : GOLD 0.03μm MIN.	4	PS	(EMBOSSD CARRIER TAPE)				
		UNDER PLATING : NICKEL 2μm MIN.	3	STAINLESS STEEL	SELECTIVE AREA : GOLD 0.03μm MIN.				
1	PPS	UL94V-0 (BLACK)			UNDER PLATING : NICKEL 0.2μm MIN.				
NO.		MATERIAL	FINISH , REMARKS		NO.		MATERIAL	FINISH , REMARKS	
UNITS mm			SCALE 4 : 1	COUNT  7	DESCRIPTION OF REVISIONS DIS-E-00011412		DESIGNED KN. ICHIKAWA	CHECKED KG. OKITA	DATE 20221102
 HIROSE ELECTRIC CO., LTD.			APPROVED : A0. SUZUKI	20060510	DRAWING NO. EDC3-046586-03				
			CHECKED : NF. MIYAZAKI	20060510	PART NO. 3260-8S3(56)				
			DESIGNED : HN. ANDO	20060510	CODE NO. CL0232-0010-5-56				
			DRAWN : HN. ANDO	20060510	 1/2				

Jan.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



HRS

DRAWING NO.	EDC3-046586-03
PART NO.	3260-8S3(56)
CODE NO.	CL0232-0010-5-56

△ 2/2