


Oct.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



Note 1. Outer surface of cover case part no. ① and ② are matte finished equivalent to TH-117 (Tanazawa hakkosha Co.,Ltd.).
Except around the ditch of HRS mark.
② 2. Part no. ①, ③, ④, ⑦ are assembled together as a unit.
Part no. ②, ⑤, ⑥ are not assembled when delivered.
3. Outer diameter of applicable cable shall be $\phi 8.5 \pm 0.5$.

4	Polycarbonate	Gray, UL94V-0			
3	Stainless steel		7	Brass	Nickel plating 0.8 μ m min.
2	Polycarbonate	Gray, UL94V-0	6	Brass	Nickel plating 0.8 μ m min.
1	Polycarbonate	Gray, UL94V-0	5	Stainless steel	
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
UNITS mm		SCALE 2 : 1	COUNT 4	DESCRIPTION OF REVISIONS DIS-E-00009711	DESIGNED KG. OKITA
		APPROVED : HO. MIWA	20051017	DRAWING NO.	EDC-040857-60-01
		CHECKED : YH. ENAMI	20051014	PART NO.	FI-20-CV(60)
		DESIGNED : TU. TANIGUCHI	20051014	CODE NO.	CL0230-0501-4-60
		DRAWN : YK. SATO	20050907		