



Apr.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




RECOMMENDED LAND PATTERN DIMENSION OF PCB
(RECOMMENDED METAL MASK THICKNESS: 0.15mm)




- NOTES
- 6 HATCHED PARTS: GROUND CIRCUIT.
 - 2 HATCHED PARTS: GROUND CIRCUIT.
 - SMT LEAD-COPLANARITY: 0.1 MAX.
 - THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.
 - MAKE SURE WIDTH OF PATTERN IS WITHIN THAT OF LAND. OR LEAD MAY TOUCH PATTERN. (THIS APPLIES TO HATCHED AREA.)
 - TO BE EMBOSSED CARRIER TAPED AS SPECIFIED IN SHEET 2.
 - THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

A-A (10:1)



B-B (10:1)







3	Phosphor bronze	Tin reflow plating 1μm MIN			
2	Phosphor bronze	Contact: Gold plating 0.1μm MIN	6	PET	Top cover tape
		Lead : Gold plating 0.03μm MIN	5	PET	Embossed carrier tape
		Under :Nickel plating 1μm MIN	4	Phosphor bronze	Surface: Tin plating 1μm MIN
1	LCP	Beige, UL94V-0			Under :Nickel plating 1μm MIN
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS

UNITS mm		SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
		5:1		1	DIS-F-00005925	MT. ITANO	HT. YAMAGUCHI

	HIROSE ELECTRIC CO., LTD.	APPROVED : HS. OKAWA	20081106	DRAWING NO.	EDC-152632-91-21	
		CHECKED : HT. YAMAGUCHI	20081106	PART NO.	FX11A-60S/6-SV(91)	
		DESIGNED : SY. KAMIGA	20081106	CODE NO.	CL573-0702-9-91	
		DRAWN : HK. SUNADORI	20081105			

--	--


$$A(5:1)$$


- NOTES 1 1REEL:1000 CONNECTORS.
2 MINIMUM 10 COMPARTMENTS FROM BOTH REEL ENDS REMAIN EMPTY.
3 THIS PRODUCT HAS NO POLARITY TO TAPE AND REEL PACKAGING.
4 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

DRAWING NO.	EDC-152632-91-21		
PART NO.	FX11A-60S/6-SV(91)		
CODE NO.	CL573-0702-9-91		$\frac{2}{2}$