








Nov.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- Note
- 1 This product is packaged in tray. (42pcs/tray)
 - 2 Blemish and hit mark can be occurred through out the manufacturing process which doesn't affect quality level. Also, black spot could be observed on the surface of housing.
 - 3 For the contact No., adjacent two pairs of leads placed back-to-back (4 leads in total) compose one line.
 - 4 Misalignment absorbing range: ± 0.3 mm max.
 - 5 The dimension in parentheses are for references.
 - 6 Lot No. is indicated at either one of the position as shown.
 - 7 UL (File No. E52653)
C-UL (File No. E52653)
TUV (Certificate No. R50275872) authorization article.



2	COPPER ALLOY	CONTACT AREA: GOLD-PLATING 0.1 μ m	4	POLYSTYRENE	
		LEAD AREA: TIN-PLATING 1.0 μ m			
		UNDER PLATING: NICKEL 1.0 μ m			
1	POLYAMIDE	BLACK UL94V-0	3	PHOSPHOR BRONZE	TIN-PLATING 3.0 μ m
NO. MATERIAL		FINISH . REMARKS	NO. MATERIAL		FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 1		DESCRIPTION OF REVISIONS
DIS-F-00006019		DESIGNED AK. IWAHORI		CHECKED HT. YAMAGUCHI	
DATE 20200406		DRAWING NO. EDC3-347273-00		PART NO. FX30B-3S-3.81DSA	
APPROVED : HS. OKAWA 20130313		CHECKED : KI. HIROKAWA 20130312		DESIGNED : DK. AIMOTO 20130311	
DRAWN : DK. AIMOTO 20130311		CODE NO. CL570-3501-4-00		1/2	

