

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
△					△						

NOTES

- THE RECOMMENDED CLAMP TORQUE OF REF. NO. ⑥ TO BE 2 N·m. LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑥ FROM LOOSENING.
- WHEN MOUNTED ON CHASSIS, BE CAREFUL THAT REFERENCE REF.NO. ⑦ IS FITTED INTO THE INDICATED GROOVE WITHOUT ANY BITING.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
4	POLYAMIDE	(BLACK) UL94V-0	7	CHLOROPRENE RUBBER	(BLACK)
3	PHOSPHOR BRONZE	SILVER PLATING:2μm min.	6	BRASS	NICKEL PLATING
2	PHOSPHOR BRONZE	SILVER PLATING:2μm min.	5	PHOSPHOR BRONZE	NICKEL PLATING
1	BRASS	NICKEL PLATING			

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M. Sato	T. Kuri	E. Kuri	M. Sato	
	07.03.26	07.03.26	07.03.27	07.03.28	

DRAWING NO.	PART NO.
EDC4-028240-73	HR10A-10WTR-12S(73)

SCALE	UNITS	CODE NO.
2 : 1	mm	CL110-1104-7-73

HIROSE ELECTRIC CO., LTD.

1

2

3

4

FORM NO. 228