


1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS		BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS		BY	CHKD	DATE
1	DIS-C-000585		T.K	E.K	07.07.27						. . .
											. . .
											. . .



NOTE ① THE RECOMMENDED CLAMP TORQUE OF REF. NO. ⑦ TO BE 2 N · m.
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO
PREVENT REF. NO. ⑦ FROM LOOSENING.

			7	BRASS ①	NICKEL PLATING
3	POLYAMIDE	(BLACK) UL94V-0	6	PHOSPHOR BRONZE	NICKEL PLATING
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	OVER PLATING:GOLD 0.2μ m min. UNDER PLATING:2μ m min.
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	PHOSPHOR BRONZE	
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS

CODE NO. (OLD) CL		DRAWN M.SATO '07 03 07	DESIGNED TO.HORII '07 03 07	CHECKED E.KUNII '07 03 08	APPROVED M.SATO '07 03 08	RELEASED
----------------------	--	------------------------------	-----------------------------------	---------------------------------	---------------------------------	----------

	DRAWING NO. EDC4-010387-72	PART NO. HR10A-10R-12S(72)	
	SCALE 2 : 1	CODE NO. CL110-0403-2-72	
	UNITS mm	1 1	