

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
△					△						

A

B

C

D

E

F

A

B

C

D

E

F

DETAIL OF MOUNTING GUIDE

PANEL CUTOUT
t=0.7 TO 2

NOTE 1 THE RECOMMENDED CLAMP TORQUE, REF. NO. ⑥ : 1.5N · m.
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO
PREVENT REF. NO. ⑥ FOR LOOSENING.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	POLYAMIDE	(BLACK) UL94V-0	6	BRASS	NICKLE PLATING
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	BRASS	OVER PLATING: GOLD 0.2μ m min. UNDER PLATING: NICKEL 2μ m min.

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M. Sato	J. Horii	M. Sato	M. Sato	
	07.03.07	07.03.06	07.03.07	07.03.07	

SCALE	DRAWING NO.	PART NO.	CODE NO.
2 : 1	EDC4-020541-74	HR10A-7R-6P(74)	CL110-0308-1-74
UNITS mm	HIROSE ELECTRIC CO., LTD.		1/1

FORM NO. 228