

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
△					△						

DETAIL OF MOUNTING GUIDE

PANEL CUTOUT
t=0.7 TO 2

B-B

1
2
5 ATTACHED
1
6 ATTACHED
3 PRESS FITTING
4 PRESS FITTING

SOLDER CUP INSIDE DIA. (ϕ 0.8)

NOTE 1 THE RECOMMENDED CLAMP TORQUE, REF.NO. ⑥ : 1.5N · m.
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF.NO. ⑥ FOR LOOSENING.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	POLYAMIDE	(BLACK) UL94V-0	6	BRASS	NICKEL PLATING
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	BRASS	OVER PLATING: GOLD 0.2 μ m min. UNDER PLATING: NICKEL 2 μ m min.

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M. Sato	T. Hara	E. Kuni	M. Sato	
	07.03.22	07.03.23	07.03.24	07.03.28	

SCALE	DRAWING NO.	PART NO.
2 : 1	EDC4-042705-74	HR10G-7R-4P(74)
UNITS	CODE NO.	
mm	CL110-1602-4-74	1/1

HIROSE ELECTRIC CO., LTD.

TO
R