


Sep.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- Notes
- 1 This product is delivered disassembled.
 - 2 The recommended clamp torque of Ref.No. ① to be 2 to 2.5N · m.
LOCTITE 263, Henkel Japan or equivalent is recommended to prevent
Ref.No. ① from loosening.
 - 3 The cable pull and twisting strength and other characteristics may differ,
depending on the cable structure. please before the use.

2	POLYPHENYLENE SULFIDE	(BLACK)	UL94V-0					
1	BRASS	BLACK CROME PLATING		3	ACRYLONITRILE BUTADIENE RUBBER	(GRAY)		
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS			DESIGNED	CHECKED
HIROSE ELECTRIC CO., LTD.		APPROVED	HY. KOBAYASHI	18. 02. 26	DRAWING NO. EDC-110621-31-00			
		CHECKED	HY. KOBAYASHI	18. 02. 26	PART NO. JR13WCCA-7(31)			
		DESIGNED	TH. KAMEYA	18. 02. 24	CODE NO. CL114-2072-3-31			
		DRAWN	MK. INOUE	18. 02. 14				