





- Notes
- ① The recommended clamp torque of REF. No. ① to be 3 to 3.5 N·m.
LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent
REF. No. ① from loosening.
 - ② The recommended clamp torque of REF. No. ④ to be 0.65 to 0.7 N·m.
 - ③ Sealing and airtightness and oil resisting shall be tested
under mated condition with an applicable connector.

2	BRASS	NICKEL PLATING		4	STAINLESS STEEL	M3×0.5×8					
1	BRASS	CHROME PLATING		3	SILICONE RUBBER	(BLACK)					
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS					
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE		
<div>HIROSE ELECTRIC CO., LTD.</div>		APPROVED		HY. KOBAYASHI		15.08.05		DRAWING NO.		EDC-110603-72-00	
		CHECKED		HY. KOBAYASHI		15.08.05		PART NO.		JR16WCC-10(72)	
		DESIGNED		HY. KISHI		15.08.05		CODE NO.		CL114-2055-4-72	
		DRAWN		HY. KISHI		15.08.05				1	