





- Notes
- ① The recommended clamp torque of REF. No. ① to be 3 to 3.5 N·m. LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent REF. No. ① from loosening.
 - ② The recommended clamp torque of REF. No. ④ to be 0.65 to 0.7 N·m.
 - ③ Sealing and airtightness and oil resisting shall be tested under mated condition with an applicable connector.

2	BRASS	NICKEL PLATING		4	STAINLESS STEEL	M3×0.5×8		
1	BRASS	CHROME PLATING		3	SILICONE RUBBER	(BLACK)		
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS		
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED	HY. KOBAYASHI		15.08.05	DRAWING NO. EDC-110462-72-00		
		CHECKED	HY. KOBAYASHI		15.08.05	PART NO. JR16WCC-12(72)		
		DESIGNED	HY. KISHI		15.08.05	CODE NO. CL114-2056-7-72		
		DRAWN	HY. KISHI		15.08.05	 1		