





- Notes
- 1 The recommended clamp torque of REF. No. ① to be 3 to 3.5 N·m.
LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent
REF. No. ① from loosening.
 - 2 The recommended clamp torque of REF. No. ④ to be 0.65 to 0.7 N·m.
 - 3 Sealing and airtightness and oil resisting shall be tested
under mated condition with an applicable connector.

2	BRASS	NICKEL PLATING		4	STAINLESS STEEL	M3×0.5×8																	
1	BRASS	CHROME PLATING		3	SILICONE RUBBER	(BLACK)																	
NO.		MATERIAL		FINISH . REMARKS		NO.		MATERIAL		FINISH . REMARKS													
UNITS mm				SCALE 2 : 1				COUNT	DESCRIPTION OF REVISIONS			DESIGNED		CHECKED		DATE							
 HIROSE ELECTRIC CO., LTD.				APPROVED				HY. KOBAYASHI				15.08.05				DRAWING NO.				EDC-110601-72-00			
				CHECKED				HY. KOBAYASHI				15.08.05				PART NO.				JR16WCC-6(72)			
				DESIGNED				HY. KISHI				15.08.05				CODE NO.				CL114-2053-9-72			
				DRAWN				HY. KISHI				15.08.05								1			