

Sep.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1					2					3					4				
COUNT	DESCRIPTION OF REVISIONS			BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS			BY	CHKD	DATE						
△							△												
△							△												
△							△												

21^{+0.1}/_{-0.2}

17.5±0.5

(ø8.6)

23±0.5

M20×0.75

(ø8)

1

2

3

4

ATTACHED

1 THE RECOMMENDED CLAMP TRQUE OF REF.① TO BE 3 TO 3.5 N·m
LOCTITE 271, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDND TO PREVENT
REF, NO.① FROM LOOSENING.

2 THE RECOMMENDED CLAMP TRQUE OF REF.④ TO BE 0.65 TO 0.7 N·m

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
2	PPS	(BLACK) UL94V-0	4	STAINLESS STEEL	M3×0.5×8
1	BRASS	BLACK CHROME PLATING	3	NBR	(GRAY)

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	J. Nori	H. Nagano	E. Kuni	M. Sato	
	05.12.20	05.12.20	05.12.20	05.12.21	

DRAWING NO.	PART NO.
EDC4-110602-71	JR16WCC-8(71)

SCALE	UNITS	CODE NO.
2 : 1	mm	CL114-2054-1-71

HRS HIROSE ELECTRIC CO., LTD.

FORM NO. 228

