





- NOTES
- 1 THE RECOMMENDED CLAMP TORQUE OF REF.NO. ① TO BE 3~3.5 N ·m.
LOCTITE 263,HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF.NO. ① FROM LOOSENING.
 - 2 THE RECOMMENDED CLAMP TORQUE OF REF.NO. ④ TO BE 0.65 TO 0.7 N ·m.
 - 3 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER,DEPENDING ON THE CABLE STRUCTURE. PLEASE CONFIRM BEFORE THE USE.

2	BRASS	NICKEL PLATING		4	STAINLESS STEEL	M3x0.5x8		
1	BRASS	CHROME PLATING		3	SILICONE RUBBER	(BLACK)		
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED :EJ. KUNII		13. 03. 19	DRAWING NO.	EDC4-110602-72		
		CHECKED :EJ. KUNII		13. 03. 19	PART NO.	JR16WCC-8(72)		
		DESIGNED :HY. KISHI		13. 03. 19	CODE NO.	CL114-2054-1-72		
		DRAWN :HY. KISHI		13. 03. 19	 1			