







COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE



RECOMMENDED P.C.B HOLE PATTERN(t=1.6±0.1)



LOT NO. MARKING

HRS No.	PART NO.	NUMBER OF CONTACT	A	B	C	D	E
583-0139-9-72	PCN10-20P-2.54DSA(72)	20	43.30	38.10	32.10	29.47	22.86
583-0007-8-72	PCN10-32P-2.54DSA(72)	32	58.54	53.34	47.34	44.71	38.10
583-0488-8-72	PCN10-44P-2.54DSA(72)	44	73.78	68.58	62.58	59.95	53.34
583-0008-0-72	PCN10-50P-2.54DSA(72)	50	81.40	76.20	70.20	67.57	60.96
583-0009-3-72	PCN10-64P-2.54DSA(72)	64	99.18	93.98	87.98	85.35	78.74
583-0010-2-72	PCN10-90P-2.54DSA(72)	90	132.20	127.00	121.00	118.37	111.76
583-0251-9-72	PCN10-100P-2.54DSA(72)	100	144.90	139.70	133.70	131.07	124.46

NOTE 1. AS FOR AUG, 2005.
2. THE DIMENSION IN PARENTHESIS IS FOR REFERENCE.

2,3	BRASS	CONTACT AREA: Ni2.5μ m+ Au0.2μ m
1	PBT	MOUNTING AREA: Ni2.5μ m+ Sn2μ m

CODE NO. (OLD)	CL	CODE NO. (NEW)	CL	FINISH, REMARKS

DRAWING NO.	EDC3-154145-01	PART NO.	PCN10-*P-2.54DSA(72)
SCALE	2:1	DESIGNED	H. SAITOU
UNITS	mm	CHECKED	S. Yamada
		APPROVED	K. Hayama
		RELEASED	

CODE NO.	CL583	FORM NO.	NO.229
----------	-------	----------	--------