

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
△					△						

Technical drawing of a connector assembly. The drawing includes a cross-section view (top) and a side view (bottom). The cross-section view shows a central pin (1) with a diameter of $\phi 0.7^{+0.05}_{-0.15}$ and a length of 5 ± 0.2 . It is surrounded by a sleeve (2) with a diameter of $\phi 2.65^{+0}_{-0.05}$ and a length of 6.75 ± 0.2 . The sleeve is secured by a nut (3) with a diameter of $\phi 0.7^{+0.05}_{-0.15}$ and a length of 4.5 ± 0.2 . The nut is secured by a washer (4) with a diameter of $\phi 0.7^{+0.05}_{-0.15}$ and a length of 4.5 ± 0.2 . The washer is secured by a nut (5) with a diameter of $\phi 0.7^{+0.05}_{-0.15}$ and a length of 4.5 ± 0.2 . The side view shows the overall dimensions of the assembly, including a total length of 4.5 ± 0.2 and a mounting hole diameter of $\phi 0.8^{+0.1}_{-0}$.

RECOMMENDED MOUNTING HOLE PATTERN

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	PHOSPHOR BRONZE	GOLD PLATED	5	BRASS	NICKEL PLATED
2	PTFE		4	PTFE	
1	BRASS	GOLD PLATED			

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	H. Fukuuchi	H. Fukuuchi	K. Shimizu	I. Mitani	
RoHS COMPLIANT	07.06.22	07.06.22	07.06.22	07.06.25	

SCALE	DRAWING NO.	PART NO.
5 : 1	EDC4-310262	PL75-LR-PC
UNITS	CODE NO.	
mm	CL334-0075-1	1/1

HRS HIROSE ELECTRIC CO., LTD.