





ELV, RoHS COMPLIANT



△ PACKING STYLE



△ DRAWING FOR REEL (FREE)



NOTE 1. 15,000 PCS PER REEL.

2. REGARDING HOW TO HANDLE THE PACKAGED PRODUCTS, PLEASE REFER TO THE ATAD-T0946-00 「INSTRUCTION MANUAL FOR HANDLING OF REEL PACKAGING CONTAINING CRIMP TERMINALS」.

△ 3. PLEASE REFER TO INSTRUCTION SHEET ETAD-T0668-00 AND ETAD-T0670-00 BEFORE USE.

1	COPPER ALLOY	SURFACE : TIN PLATING $1\mu\text{m min}$ UNDER PLATING : COPPER PLATING $0.3\mu\text{m min}$						
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS	
UNITS mm		SCALE 5:1	COUNT 4	DESCRIPTION OF REVISIONS DIS-T-00018293	DESIGNED AS. SHIBAHARA	CHECKED TY. MOGI	DATE 2023. 06. 03	
HIROSE ELECTRIC CO., LTD.		APPROVED : AH. EDASHIGE	2018. 06. 26	DRAWING NO. EDC-372040-00-00				
		CHECKED : AH. EDASHIGE	2018. 06. 26	PART NO. ZE064-2022PCF				
		DESIGNED : HH. TSUKUMO	2018. 06. 26	CODE NO. CL0753-2002-0-00				
		DRAWN : HH. TSUKUMO	2018. 06. 26					