Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of IRA-S200ST01A01 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=IRA-S200ST01A0

## IRA-S200ST01A01











### **Applications**

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	
Recommended Applications	Intrusion detection,Security Equipment,	
	Light,Indoor,For Wall,Improved RF	
	immunity	



#### Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	Вох	100




#### **Features**

Excellent Sensitivity & S/N ratio (Signal/Noise) Excellent Quality Excellent EMC



#### Appearance & Shape





1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# IRA-S200ST01A01

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of IRA-S200ST01A01 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=IRA-S200ST01A0



## **Specifications**

Shape	Lead
Dimensions	TO-5(φ9.2x4.7mm)
Output Type	Analog
Electrode	(2.0x1.0mm)x2
Responsivity(typ.)	4.6mV
Supply Voltage Range	2V to 15V
Field of View	X-axis/Y-axis=45deg.
Operating Temperature (°C)	-40°C to 70°C
Storage Temperature Range	-40°C to 85°C

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no space for \ detailed \ specifications.}$ 

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




#### Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of IRA-S200ST01A01 from the official website of Murata

# IRA-S200ST01A01






(in mm)



Pyroelectric Elements(Electrode Dimension)

Optical Filter characteristics



Test system of Responsivity

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

