





#### **FEATURES**

- RoHS compliant
- Sub-miniature SIP & DIP styles
- 3kVDC isolation 'Hi Pot Test'
- UL60950 recognised
- Wide temperature performance at full 1 Watt load. —40°C to 85°C
- UL 94V-0 package material
- Footprint at 0.69cm<sup>2</sup>
- Industry standard pinout
- 3.3V, 5V & 12V inputs
- 3.3V, 5V, 9V, 12V & 15V outputs
- Internal SMD construction
- Fully encapsulated with toroidal magnetics
- MTTF up to 2.4 million hours
- Custom solutions available
- No electrolytic or tantalum capacitors

#### **PRODUCT OVERVIEW**

The NKE sub-miniature series of DC-DC Converters is particularly suited to isolating and/or converting DC power rails. A smaller package size, improved efficiency, lower output ripple and 3kVDC isolation capability through state of the art packaging and improved technology. The galvanic isolation allows the device to be configured to provide an isolated negative rail in systems where only positive rails exist. The wide temperature range guarantees startup from -40°C and full 1 watt output at 85°C.

SELECTION 6	UIDE										
Order Code	Nominal Input Voltage	Output Voltage	Output Current	Input Current at Rated Load	- Efficiency		Isolation Capacitance	i.	ī. I.	Package Style	Recommended Alternative
	V	V	mA	mA	9	6	pF	MIL.	Tel.		
	V	V	IIIA	IIIA	Min.	Тур.	þΓ	kl	Hrs		
			Re	comn	nended	In P	rodu	ction			
NKE0303DC	3.3	3.3	303	400	68	72	30	4337	46,969	DID	
NKE0305DC	3.3	5	200	400	72	75	35	4105	46,783	DIP	
NKE0303SC	3.3	3.3	303	400	68	72	30	4337	46,969	CID	
NKE0305SC	3.3	5	200	400	72	75	35	4105	46,783	SIP	
NKE0503DC	5	3.3	303	270	70	74	40	3710	36,234		
NKE0505DC	5	5	200	289	66	69	28	4277	34,897	DIP	
NKE0512DC	5	12	83	260	73	78	30	2910	73,523		
NKE0503SC	5	3.3	303	270	70	74	40	3710	36,234		
NKE0505SC	5	5	200	289	66	69	28	4277	34,897		
NKE0505SEC	5	5	200	250	73	77	34	2686	35,919	CID	
NKE0509SC	5	9	111	266	72	75	29	3729	76,553	SIP	
NKE0512SC	5	12	83	260	73	78	30	2910	73,523		
NKE0515SC	5	15	66	256	74	78	32	2211	71,725		
NKE1205DC	12	5	200	117	68	72	35	3981	58,202	DID	
NKE1212DC	12	12	83	105	73	79	57	1982	77,806	DIP	
NKE1205SC	12	5	200	117	68	72	35	3981	58,202		
NKE1209SC	12	9	111	107	72	78	50	3482	57,895	SIP	
NKE1212SC	12	12	83	105	73	79	57	1982	77,806		
					Disco	ntinue	d				
NKE0309SC	3.3	9	111	403	71	74	30	1904	28,918	OID	Contact Murata
NKE1215SC	12	15	66	103	76	81	60	2122	56,404	SIP	NME1215SC
NKE0309DC	3.3	9	111	403	71	74	30	1904	28,918		Contact Murata
NKE0505DEC	5	5	200	250	73	77	34	2686	35,919		NME0505DC
NKE0509DC	5	9	111	266	72	75	29	3729	76,553	DID	NME0509SC
NKE0515DC	5	15	66	256	74	78	32	2211	71,725	DIP	CRE1S0515SC
NKE1209DC	12	9	111	107	72	78	50	3482	57,895		NKE1209SC
NKE1215DC	12	15	66	103	76	81	60	2122	56,404		NME1215SC
NKE0505SEC/NKI	E0505DE0	C offers h	igher effi	ciency tha	n NKE050	SC/NKE05	05DC b	ut over a	narrower (	perating	temperature range.

INPUT CHARACTERISTICS								
Parameter	Min.	Тур.	Max.	Units				
	Continuous operation, 3.3V input types	2.97	3.3	3.63				
Voltage range	Continuous operation, 5V input types	4.5	5.0	5.5	V			
	Continuous operation, 12V input types	10.8	12.0	13.2				
Reflected ripple current	3.3V input types		40	60	mA p-p			







See temperature characteristics graph.

1.Calculated using MIL-HDBK-217 FN2 and Telcordia SR-332 calculation model with nominal input voltage at full load. All specifications typical at Ta=25°C, nominal input voltage and rated output current unless otherwise specified.



Isolated Sub-Miniature 1W Single Output DC-DC Converters

GENERAL CHARACTERISTICS					
Parameter	Conditions	Min.	Тур.	Max.	Units
Switching frequency	All output types		115		kHz

<b>OUTPUT CHARACTERISTIC</b>	S					
Parameter	Conditions	Min.	Тур.	Max.	Units	
Rated Power	T <sub>A</sub> =-40°C to 120°C, see derating graphs			1.0	W	
Voltage Set Point Accuracy	See tolerance envelope					
Line regulation	High Vin to low Vin		1.0	1.2	%/%	
	10% load to rated load, 3.3V output types & 0309		10	15		
	10% load to rated load, 5V output types		12	15	i	
Load Regulation <sup>1</sup>	10% load to rated load, 9V output types		7.5	10	%	
	10% load to rated load, 12V output types		6.5	9.5		
	10% load to rated load, 15V output types		6.0	8.5		
	BW=DC to 20MHz, 3.3V output types & 0305, 0505SEC, 0505DEC		40	80		
	BW=DC to 20MHz, other 5V output types		77	100		
Ripple and Noise	BW=DC to 20MHz, 9V output types		43	90	mV p-p	
	BW=DC to 20MHz, 12V output types		35	65	65	
	BW=DC to 20MHz, 15V output types		32	55		

ISOLATION CHARACTERISTICS								
Parameter	Conditions	Min.	Тур.	Max.	Units			
Isolation test voltage	Flash tested for 1 second	3000			VDC			
Resistance	Viso= 1000VDC		10		GΩ			

TEMPERATURE CHARACTERISTICS							
Parameter	Conditions	Min.	Тур.	Max.	Units		
Specification	All output types, See safety approval section for UL temperature specification <sup>1</sup>	-40		85			
Storage		-50		130	°C		
Case temperature rise above	0505D/S, 1205D/S			41	U		
ambient	All other output types			32			
Cooling	Free air convection						

ABSOLUTE MAXIMUM RATINGS	
Lead temperature 1.5mm from case for 10 seconds	260°C
Wave Solder	Wave Solder profile not to exceed the profile recommended in IEC 61760-1 Section 6.1.3. Please refer to application notes for further information.
Input voltage V <sub>IN</sub> , NKE03 types	5.5V
Input voltage V <sub>IN</sub> , NKE05 types	7V
Input voltage V <sub>IN</sub> , NKE12 types	15V

<sup>1. 12</sup>V input types have typically 3% less load regulation.



Isolated Sub-Miniature 1W Single Output DC-DC Converters

### **TECHNICAL NOTES**

#### **ISOLATION VOLTAGE**

'Hi Pot Test', 'Flash Tested', 'Withstand Voltage', 'Proof Voltage', 'Dielectric Withstand Voltage' & 'Isolation Test Voltage' are all terms that relate to the same thing, a test voltage, applied for a specified time, across a component designed to provide electrical isolation, to verify the integrity of that isolation.

Murata Power Solutions NKE series of DC-DC converters are all 100% production tested at their stated isolation voltage. This is 3000V DC for 1 second.

A question commonly asked is, "What is the continuous voltage that can be applied across the part in normal operation?"

The NKE series has been recognised by Underwriters Laboratory for functional insulation. Both input and output should normally be maintained within SELV limits i.e. less than 42.4V peak, or 60VDC. The isolation test voltage represents a measure of immunity to transient voltages and the part should never be used as an element of a safety isolation system. The part could be expected to function correctly with several hundred volts offset applied continuously across the isolation barrier; but then the circuitry on both sides of the barrier must be regarded as operating at an unsafe voltage and further isolation/insulation systems must form a barrier between these circuits and any user-accessible circuitry according to safety standard requirements.

#### REPEATED HIGH-VOLTAGE ISOLATION TESTING

It is well known that repeated high-voltage isolation testing of a barrier component can actually degrade isolation capability, to a lesser or greater degree depending on materials, construction and environment. While manufactured parts can withstand several times the stated test voltage, the isolation capability does depend on the wire insulation. Any material, including this enamel (typically polyurethane) is susceptible to eventual chemical degradation when subject to very high applied voltages thus implying that the number of tests should be strictly limited. We therefore strongly advise against repeated high voltage isolation testing, but if it is absolutely required, that the voltage be reduced by 20% from specified test voltage.


#### **ROHS COMPLIANCE INFORMATION**



This series is compatible with RoHS soldering systems with a peak wave solder temperature of 260°C for 10 seconds. Please refer to application notes for further information. The pin termination finish on the SIP package type is Tin Plate, Hot Dipped over Matte Tin with Nickel Preplate. The DIP types are Matte Tin over Nickel Preplate. Both types in this series are backward compatible with Sn/Pb soldering systems. For further information, please visit https://www.murata.com/en-global/products/power/rohs

## SAFETY APPROVAL

The NKE series has been recognised by Underwriters Laboratory (UL) to UL 60950 for functional insulation in a maximum ambient temperature of 85°C and/or case temperature limit of 130°C. Case temperature measured on the face opposite the pins. File number E151252 applies.






## **CHARACTERISATION TEST METHODS**

#### Ripple & Noise Characterisation Method

Ripple and noise measurements are performed with the following test configuration.

C1	1μF X7R multilayer ceramic capacitor, voltage rating to be a minimum of 3 times the output voltage of the DC-DC converter				
C2	$10\mu F$ tantalum capacitor, voltage rating to be a minimum of 1.5 times the output voltage of the DC-DC converter with an ESR of less than $100 \text{m}\Omega$ at $100 \text{kHz}$				
C3	100nF multilayer ceramic capacitor, general purpose				
R1	$450\Omega$ resistor, carbon film, ±1% tolerance				
R2	$50\Omega$ BNC termination				
T1	3T of the coax cable through a ferrite toroid				
RLOAD	Resistive load to the maximum power rating of the DC-DC converter. Connections should be made via twisted wires				
Measured values are multiplied by 10 to obtain the specified values.					

#### Differential Mode Noise Test Schematic



## APPLICATION NOTES

#### Minimum load

The minimum load to meet datasheet specification is 10% of the full rated load across the specified input voltage range. Lower than 10% minimum loading will result in an increase in output voltage, which may rise to typically double the specified output voltage if the output load falls to less than 5%.


## Capacitive loading and start up

Typical start up times for this series, with a typical input voltage rise time of 2.2 $\mu$ s and output capacitance of 10 $\mu$ F, are shown in the table below. The product series will start into a capacitance of 47 $\mu$ F with an increased start time, however, the maximum recommended output capacitance is 10 $\mu$ F.

	Start-up time
	μs
NKE0303SC	544
NKE0305SC	1306
NKE0309SC	5250
NKE0503SC	496
NKE0505SC	1075
NKE0505SEC	894
NKF0509SC	3140

	Start-up time
	μs
NKE0512SC	5040
NKE0515SC	9940
NKE1205SC	1671
NKE1209SC	2835
NKE1212SC	5295
NKE1215SC	8475

#### Typical Start-Up Wave Form







## **APPLICATION NOTES (Continued)**

#### Output Ripple Reduction


By using the values of inductance and capacitance stated, the output ripple at the rated load is lowered to 5mV p-p max.

#### Component selection

Capacitor: It is required that the ESR (Equivalent Series Resistance) should be as low as possible, ceramic types are recommended.

The voltage rating should be at least twice (except for 15V output), the rated output voltage of the DC-DC converter.

Inductor: The rated current of the inductor should not be less than that of the output of the DC-DC converter. At the rated current, the DC resistance of the inductor should be such that the voltage drop across the inductor is <2% of the rated voltage of the DC-DC converter. The SRF (Self Resonant Frequency) should be >20MHz.




		Inductor		Capacitor
	L, μH	SMD	Through Hole	C, µF
NKE0303xC	10	82103C	11R103C	4.7μF
NKE0305xC	47	82473C	11R473C	4.7μF
NKE0309xC	47	82473C	11R473C	1μF
NKE0503xC	10	82103C	11R103C	4.7μF
NKE0505xC	47	82473C	11R473C	4.7μF
NKE0505xEC	47	82473C	11R473C	4.7μF
NKE0509SC	47	82473C	11R473C	1μF
NKE0512xC	68	82683C	11R683C	0.68µF
NKE0515xC	100	82104C	11R104C	2.2µF
NKE1205xC	47	82473C	11R473C	4.7μF
NKE1209xC	47	82473C	11R473C	1μF
NKE1212xC	68	82683C	11R683C	0.47µF
NKE1215xC	100	82104C	11R104C	2.2µF






### **TOLERANCE ENVELOPES**

The voltage tolerance envelope shows typical load regulation characteristics for this product series. The tolerance envelope is the maximum output voltage variation due to changes in output loading.







## TEMPERATURE DERATING GRAPHS

NKE 0303DC/SC, 0305DC/ SC, 0309DC/SC, 0503DC/SC, 0505DEC/SEC types only.


UL recognition to a maximum ambient temperature of 85°C and/ or case temperature limit of 130°C.








Isolated Sub-Miniature 1W Single Output DC-DC Converters











Isolated Sub-Miniature 1W Single Output DC-DC Converters

#### DISCLAIMER

Unless otherwise stated in the datasheet, all products are designed for standard commercial and industrial applications and NOT for safety-critical and/or life-critical applications.

Particularly for safety-critical and/or life-critical applications, i.e. applications that may directly endanger or cause the loss of life, inflict bodily harm and/or loss or severe damage to equipment/property, and severely harm the environment, a prior explicit written approval from Murata is strictly required. Any use of Murata standard products for any safety-critical, life-critical or any related applications without any prior explicit written approval from Murata shall be deemed unauthorised use.

These applications include but are not limited to:

- Aircraft equipment
- Aerospace equipment
- Undersea equipment
- Power plant control equipment
- Medical equipment
- Transportation equipment (automobiles, trains, ships, etc.)
- Traffic signal equipment
- Disaster prevention / crime prevention equipment
- Data Processing equipment

Murata makes no express or implied warranty, representation, or guarantee of suitability, fitness for any particular use/purpose and/or compatibility with any application or device of the buyer, nor does Murata assume any liability whatsoever arising out of unauthorised use of any Murata product for the application of the buyer. The suitability, fitness for any particular use/purpose and/or compatibility of Murata product with any application or device of the buyer remain to be the responsibility and liability of the buyer.

Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards that anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm, and take appropriate remedial actions. Buyer will fully indemnify and hold Murata, its affiliated companies, and its representatives harmless against any damages arising out of unauthorised use of any Murata products in any safety-critical and/or life-critical applications.

Remark: Murata in this section refers to Murata Manufacturing Company and its affiliated companies worldwide including, but not limited to, Murata Power Solutions.



This product is subject to the following <u>operating requirements</u> and the <u>Life and Safety Critical Application Sales Policy</u>:

Refer to: https://www.murata.com/en-eu/products/power/requirements

Murata Power Solutions (Milton Keynes) Ltd. makes no representation that the use of its products in the circuits described herein, or the use of other technical information contained herein, will not infringe upon existing or future patent rights. The descriptions contained herein on timply the gradness therein gold in expectation are thereith. Specifications are subject to change without notice.