




5/16 Round Spacers



Hex Code Table

✓	FMXXXX	Length (L)
	FC1153	1/8
	FC1154	3/16
	FC1155	1/4
	FC1156	5/16
	FC1157	3/8
	FC1158	7/16
	FC1159	1/2
	FC1160	9/16
	FC1161	5/8
	FC1162	11/16
	FC1163	3/4
	FC1164	13/16
	FC1165	7/8
	FC1166	15/16
	FC1167	1
	FC1168	1-1/16
	FC1169	1-1/8
	FC1170	1-3/16
	FC1171	1-1/4
	FC1172	1-5/16
	FC1173	1-3/8
	FC1174	1-7/16
	FC1175	1-1/2
	FC1176	1-9/16
	FC1177	1-5/8
	FC1178	1-11/16
	FC1179	1-3/4
	FC1180	1-13/16
	FC1181	1-7/8
	FC1182	1-15/16
	FC1183	2

Create a part number:

Length	Clearance	Material	Finish
FCXXXX	XX	XX	XX
_____	_____	_____	_____

Hole Clearance Code (XX)

✓	Code (XX)	C + .010
	4	.115
	6	.140
	8	.166
	10	.192

Material

✓	Material Code (XX)
A	Aluminum
B	Brass
S	Steel
SS	Stainless Steel
N	Nylon

Compatible Finish (XX)

✓	Compatible Finish (XX)
A, B, S, SS	0 - Plain
B, S	5 - Nickel Plate (QQ-N-290)
A	6 - Iridite #14 Gold (MIL-C-5541E)
A	7 - Iridite Clear (MIL-C-5541E)
A	9 - Alodine 1200
B, S	12 - Zinc Clear (ASTM-B-633)
B, S	16 - Electro Tin (MIL-T-10727 TYPE 1)
SS	20 - Passivation (MIL-F-14072D)
A	22 - Clear Anodize (MIL-A-8625-TYPE2) (Sulphuric) Hot Water Seal (Clear)
A	24 - Black Anodize (MIL-A-8625)
B, S, SS	26 - Black Oxide
B, S	28 - Zinc Yellow (ASTM-B-633)



Tolerances
Unless otherwise Specified
 .xxx +/- .005
 .xx +/- .010
 Angular +/- 1 Degree
 Linear +/- .005
Break all sharp edges

Source Control Drawing:
 To be produced by
 Fascomp Electronic Hardware

This document is the property of Fascomp Inc. and shall not be reproduced, distributed, or used as a basis for manufacturing without written permission from Fascomp Inc.