

## Voltage Controlled Oscillator 8.4 - 9.25 GHz

Rev. V4

### Features

- Low Phase Noise
- Wide Tuning Range
- Divide-by-Two Output
- Integrated Buffer Amplifier
- Excellent Temperature Stability
- +5V Bias Supply
- Lead-Free 5 mm 32-Lead PQFN Package
- Halogen-Free “Green” Mold Compound
- RoHS\* Compliant and 260°C Reflow Compatible

### Description

The MAOC-010334 is an InGaP HBT-based voltage controlled oscillator for frequency generation. No external matching components are required. This VCO is easily integrated into a phase lock loop using the divide-by-two output. The extremely low phase noise makes this part ideal for many radio applications including high capacity digital radios.

The MAOC-010334 primary applications are Point-to-Point Radio, Point-to-Multipoint Radio, Communications Systems, and Low Phase Noise applications.


The 5 mm PQFN package has a lead-free finish that is RoHS compliant and compatible with a 260°C reflow temperature. The package also features low lead inductance and an excellent thermal path.

### Ordering Information<sup>1</sup>

Part Number	Package
MAOC-010334-TR0500	500 piece reel
MAOC-010334-TR1000	1000 piece reel
MAOC-010334-001SMB	Sample Board

1. Reference Application Note M513 for reel size information.

### Block Diagram



### Pin Designations<sup>2</sup>

Pin	Function	Pin	Function
1	N/C	17	N/C
2	N/C	18	N/C
3	N/C	19	RF
4	N/C	20	N/C
5	N/C	21	V <sub>CC</sub>
6	N/C	22	N/C
7	V <sub>BUFFER</sub>	23	N/C
8	N/C	24	N/C
9	N/C	25	N/C
10	N/C	26	N/C
11	N/C	27	N/C
12	RF/2	28	N/C
13	N/C	29	V <sub>TUNE</sub>
14	N/C	30	N/C
15	N/C	31	N/C
16	N/C	32	N/C

2. The exposed pad centered on the package bottom must be connected to RF and DC ground. Connecting all N/C pins to RF/DC Ground in the layout is also recommended.

\* Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.

## Voltage Controlled Oscillator

### 8.4 - 9.25 GHz

Rev. V4

**Electrical Specifications:**  $T_A = +25^\circ\text{C}$ ,  $V_{CC} = V_{\text{BUFFER}} = 5.0\text{ V}^3$ ,  $Z_0 = 50\ \Omega$

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Output Power	RF Port, 8.4 - 9.25 GHz RF/2 Port, 4.2 - 4.625 GHz	dBm	6 0	10 3	—
SSB Phase Noise	RF Port, 10 KHz Offset RF Port, 100 KHz Offset	dBc/Hz	—	-88 -115	—
Harmonics/Subharmonics $V_{CC}=V_{\text{BUFFER}}=V_{\text{TUNE}}=5\text{V}$	RF Port, $\frac{1}{2} F_0$ RF Port, $2 F_0$	dBc	—	-21 -28	—
Pulling (Sensitivity to Match) $V_{CC}=V_{\text{BUFFER}}=V_{\text{TUNE}}=5\text{V}$	RF Port, VSWR = 1.95:1 to 2.25:1	MHz pk-pk	—	7	—
Pushing (Sensitivity to Supply Voltage)	RF Port, $V_{\text{TUNE}} = 5\text{ V}$ RF/2 Port, $V_{\text{TUNE}} = 5\text{ V}$	MHz/V	—	4 2	—
Frequency Drift Rate (Sensitivity to Temperature)	RF Port, 8.4 - 9.25 GHz RF/2 Port, 4.2 - 4.625 GHz	MHz/ $^\circ\text{C}$	—	0.75 0.3	—
Output Return Loss	RF Port, 8.4 - 9.25 GHz RF/2 Port, 4.2 - 4.625 GHz	dB	—	6 9	—
Tuning Sensitivity @ RF Port	$V_{\text{TUNE}} = 5\text{ V}$	GHz/V	—	0.14	—
Supply Current	$I_{\text{TOTAL}} (I_{CC} + I_{\text{BUFFER}})$ $I_{CC}$ $I_{\text{BUFFER}}$	mA	— — —	168 150 18	195 165 30
Tune Voltage	$V_{\text{TUNE}}$	V	2	—	13
Tuning Current Leakage	$V_{\text{TUNE}} = 13\text{ V}$	$\mu\text{A}$	—	7	10

3. VCO can operate over the 4.75 V to 5.25 V supply voltage range.

### Absolute Maximum Ratings <sup>4,5,6</sup>

Parameter	Absolute Maximum
Supply Voltage ( $V_{CC}$ & $V_{\text{BUFFER}}$ )	+5.5 Vdc
$V_{\text{TUNE}}$	0 to +15 Vdc
Storage Temperature	-55 $^\circ\text{C}$ to +150 $^\circ\text{C}$
Operating Temperature	-40 $^\circ\text{C}$ to +85 $^\circ\text{C}$
Case Temperature ( $T_C$ ) (measured @ exposed pad)	+100 $^\circ\text{C}$
Junction Temperature <sup>7</sup>	+135 $^\circ\text{C}$

- Exceeding any one or combination of these limits may cause permanent damage to this device.
- MACOM does not recommend sustained operation near these survivability limits.
- Operating at nominal conditions with  $T_J \leq 135^\circ\text{C}$  will ensure  $\text{MTTF} > 1 \times 10^6$  hours.
- Junction Temperature ( $T_J$ ) =  $T_C + \Theta_{jc} * (V * I)$   
Typical thermal resistance ( $\Theta_{jc}$ ) = 35 $^\circ\text{C/W}$ .  
a) For  $T_C = 25^\circ\text{C}$ ,  $T_J = 54.4^\circ\text{C}$  @ 5 V, 168 mA  
b) For  $T_C = 85^\circ\text{C}$ ,  $T_J = 115.3^\circ\text{C}$  @ 5 V, 173 mA

### Handling Procedures

Please observe the following precautions to avoid damage:

### Static Sensitivity

Gallium Arsenide Integrated Circuits are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these Class 1B devices.




**ESD Rating: Class 1B**

## Voltage Controlled Oscillator 8.4 - 9.25 GHz


Rev. V4

**Typical Performance Curves:  $V_{CC} = V_{BUFFER} = 5V$ ,  $T_A = +25^\circ C$  (unless otherwise indicated)**


**Output Frequency vs. Tuning Voltage - RF Port**




**Output Frequency vs. Tuning Voltage - RF/2 Port**




**Output Frequency vs. Tuning / Supply Voltage - RF Port**




**Output Frequency vs. Tuning / Supply Voltage - RF/2 Port**



**Output Power vs. Tuning Voltage - RF Port**



**Output Power vs. Tuning Voltage - RF/2 Port**




## Voltage Controlled Oscillator 8.4 - 9.25 GHz


Rev. V4

**Typical Performance Curves:**  $V_{CC} = V_{BUFFER} = 5V$ ,  $T_A = +25^\circ C$  (unless otherwise indicated)


**Frequency Sensitivity vs. Tuning Voltage - RF Port**




**Frequency Sensitivity vs. Tuning Voltage - RF/2 Port**



**Single Side Band Phase Noise vs. Tuning Voltage  
RF Port**




**Single Side Band Phase Noise vs. Frequency Offset  
RF Port ( $V_{TUNE} = 5V$ )**



## Rev. V4

## Parts List



Component	Value	Case Size
C1	100 pF	0402
C2, C3, C4	0.1 $\mu$ F	0402
C5	10 $\mu$ F Tantalum	1206

**Figure 1: JEDEC MO-220-VHHD-5 Dimensions**

The drawing shows the top and side views of the JEDEC MO-220-VHHD-5 package. Key dimensions and features include:

- Top View Dimensions:**
  - Overall width: 1.969 ± 0.005 in
  - Overall height: 3.2 in
  - Central body width: 1.969 ± 0.005 in
  - Central body height: 3.2 in
  - Pin pitch: 0.0354 ± 0.0039 in
  - Pin array width: 0.90 ± 0.10 in
  - Pin array height: 0.0020 in, 0.0000 in, 0.05 in, 0.00 in
  - Pin pitch (side view): 0.0098 ± 0.0020 in, 0.25 ± 0.05 in
- Side View Dimensions:**
  - Package height: 0.0020 in, 0.0000 in, 0.05 in, 0.00 in
  - Pin pitch (side view): 0.0098 ± 0.0020 in, 0.25 ± 0.05 in
- Markings:**
  - MA
  - YYWW
  - OC0334
  - LLLLLL
- Other Features:**
  - PIN#1 IDENTIFIER
  - SEATING PLATE
  - SO.
  - MIN.

**NOTES:**

1. Reference JEDEC MO-220-VHHD-5 for additional dimensional and tolerance information.
2. All dimensions shown as in/mm.
3. Reference S2083 application note for PCB footprint information.

† Reference Application Note S2083 for lead-free solder reflow recommendations.  
Meets JEDEC moisture sensitivity level 3 requirements.  
Plating is 100% matte tin over copper.

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.