


 \varnothing 0.375 \pm 0.010 [9.53 \pm 0.25]



NOTES:

- 1. Material: 2024-T3 Aluminum alloy tubing, AMS-WW-T-700/3, TYPE 1 2024-T4 Aluminum alloy wire or rod, AMS-QQ-A-225/6
- 2. Finish: CHEMICAL FILM (MIL-DTL-5541), CLASS 1A, DYED BLUE
- 3. All Drawing Dimensions are in Inches [mm]
- 4. Unless otherwise specified, edge breaks, radii or countersinks 0.005 MAX.
- 5. All features in accordance with NAS42



95 Silvermine Rd., Seymour CT 06483 Tel: 203-888-2133, Fax: 203-888-9860 This Drawing is the Property of MW Industries. It contains confidential, proprietary information that is MW Industries property. Do not disclose to or duplicate for others except as authorized by MW Industries.

TOLERANCES

ALL DIMENSIONS ARE INCHES
(UNLESS OTHERWISE SPECIFIED)

METALLIC

LENGTHS </=:6 INCHES ± 0.005
LENGTH >:6 INCHES ± 0.010
DIAMETERS: ± 0.005
NON-METALLIC
ENGTH: ± 0.010 DIAMETERS: ± 0.00

LENGTH: ±0.010 DIAMETERS: ± 0.010

INTERNAL THREADS:

MINIMUM THREAD DEPTH

NAS42DD8A-10FC

COMPONENT

3/8" Round Spacer

SPACER		
	SCALE	REV
	5.07	11
	SHEET	
	1 of 1	