






Ø 0.375 ± 0.010
[9.53 ± 0.25]



NOTES:

1. Material: 2024-T3 Aluminum alloy tubing, AMS-WW-T-700/3, TYPE 1
2024-T4 Aluminum alloy wire or rod, AMS-QQ-A-225/6
2. Finish: CHEMICAL FILM (MIL-DTL-5541), CLASS 1A, DYED BLUE
3. All Drawing Dimensions are in Inches [mm]
4. Unless otherwise specified, edge breaks, radii or countersinks 0.005 MAX.
5. All features in accordance with NAS42



MW Industries

95 Silvermine Rd., Seymour CT 06483
Tel: 203-888-2133, Fax: 203-888-9860

This Drawing is the Property of MW Industries. It contains confidential, proprietary information that is MW Industries property. Do not disclose to or duplicate for others except as authorized by MW Industries.

TOLERANCES
ALL DIMENSIONS ARE INCHES
(UNLESS OTHERWISE SPECIFIED)
METALLIC
LENGTHS < 6 INCHES ± 0.005
LENGTH > 6 INCHES ± 0.010
DIAMETERS: ± 0.005
NON-METALLIC
LENGTH: ± 0.010 DIAMETERS: ± 0.010
INTERNAL THREADS:
MINIMUM THREAD DEPTH

COMPONENT

SPACER

NAS42DD8A-40FC

3/8" Round Spacer

SCALE REV

3.04 11

SHEET

1 of 1