

- 2. Finish:
- 3. % of Thread for Tapped Holes: Form Tap 60 | Cut Tap 70
- 4: Threads are Supplied Cut or Rolled at RAF's Option Unless Noted on Order.
- 5. Threads are to Commercial 2A and 2B Standards per Handbook H-28 (Part 1)
- 6. ASME Y14.5M 2009
- 7. Remove burrs and sharp edges
- 8. Changes may occur with no notice
- 9. Nuts and washers supplied



95 Silvermine Rd., Seymour CT 06483 Tel: 203-888-2133, Fax: 203-888-9860

This Drawing is the Property of MW Industries. It contains confidential, proprietary information that is MW Industries property. Do not disclose to or duplicate for others except as authorized by MW Industries.

TOLERANCES ALL DIMENSIONS ARE INCHES (UNLESS OTHERWISE SPECIFIED) METALLIC

LENGTHS </=: 6 INCHES ± 0.005 LENGTH >: 6 INCHES ± 0.010 DIAMETERS: ± 0.005 **NON-METALLIC**

LENGTH: ±0.010 DIAMETERS: ± 0.010 INTERNAL THREADS: MINIMUM THREAD DEPTH

8888-3124-A

COMPONENT

5/8 x 9/32 OVAL 180° 3 POSITION EXTERNAL THREADED HANDLE

HANDLES SCALE 0.84 SHEET

1 of 1