

### LISA3-02-PIN

~20° x 35° oval beam with location pin installation

### **SPECIFICATION:**

Dimensions	Ø 10.0
Height	6.9 mm
Fastening	snaps
ROHS compliant	yes 🕕



### **MATERIALS:**

Component	Type	Material	Colour	Finish	Length (mm)
LISA3-O2	Single lens	PMMA	clear		
LISA3-HLD-PIN	Holder	PC	black		


### **ORDERING INFORMATION:**

Component Qty in box MOQ MPQ Box weight (kg) FP18677\_LISA3-O2-PIN 2000 300 100 1.3

» Box size: 310 x 230 x 60 mm



# PRODUCT DATASHEET FP18677\_LISA3-O2-PIN



See also our general installation guide: www.ledil.com/installation\_guide




# **OPTICAL RESULTS (MEASURED):**



LED XT-E

FWHM / FWTM 34.5 + 22.0° / 65.5 + 45.5°

Efficiency 81 % Peak intensity 2.6 cd/lm LEDs/each optic Light colour/type White Required components:



Light distribution files

Published: 05/12/2022



# **OPTICAL RESULTS (SIMULATED):**




LED SST-12 Gen1

FWHM / FWTM 39.0 + 18.0° / 66.0 + 36.0°

Efficiency 88 %
Peak intensity 3.4 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:



Light distribution files




LED SST-12 Gen2

FWHM / FWTM 40.0 + 20.0° / 68.0 + 42.0°

Efficiency 87 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:





Light distribution files




LED SST-20 Gen1

FWHM / FWTM 41.0 + 19.0° / 66.0 + 40.0°

Efficiency 85 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:



Light distribution files



### **OPTICAL RESULTS (SIMULATED):**


# **WNICHIA**

LED NV4WB35AM

FWHM / FWTM 40.0 + 30.0° / 82.0 + 66.0°

Efficiency 81 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:




Light distribution files


#### OSRAM Opto Semiconductors

LED SFH 4716S

FWHM / FWTM 40.0 + 17.0° / 61.0 + 33.0°

Efficiency 85 % LEDs/each optic 1 Light colour/type IR Required components:





Light distribution files



# PRODUCT DATASHEET FP18677\_LISA3-O2-PIN

### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

### **LEDIL Oy**

Joensuunkatu 7 FI-24100 SALO Finland

### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

### **Shipping locations**

Poznan, Poland Hong Kong, China

### **Distribution Partners**

www.ledil.com/ where\_to\_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.