



The DNA of tech.™

Standard Rectifiers in DFN3820A Package

Industry-first 2 A to 4 A, up to 600 V standard recovery rectifier in extremely low profile



ADVANTAGE

Power DFN design offers high current density and high efficiency capability with small and extremely low profile solutions

KEY PRODUCT FEATURES

- ✓ Industry-first Power DFN3820A low profile package - small dimensions of 3.8 mm x 2.0 mm with typical height of 0.88 mm
- ✓ High current and high efficiency, current rating from 2 A to 4 A for standard rectifiers, DFN3820A performance more than double under thermal equilibrium conditions compared to SMP (DO-220AA)
- ✓ Oxide planar chip junction design, reverse voltage up to 600 V with typical reverse leakage current less than 0.1 μ A and wide temperature range from -55 °C to +175 °C



RESOURCES



[Order Samples](#)



[Product Page](#)

SE20ND, SE20NG, SE20NJ



[Product Page](#)

SE30ND, SE30NG, SE30NJ



[Product Page](#)

SE40ND, SE40NG, SE40NJ



[Contact Us](#)

Diodes Americas



[Contact Us](#)

Diodes Asia



[Contact Us](#)

Diodes Europe

MARKETS & APPLICATIONS



CONNECTIVITY

- Telecom mobile and fixed infrastructure
- Telecom mobile devices



CONSUMER

- Entertainment
- Appliances
- Health and care



MOBILITY

- Automotive
- Micro mobility
- Agriculture equipment



ENERGY SECTOR

- Energy distribution and management
- Energy generation and exploration
- Energy storage



INDUSTRIAL

- Automation
- Drives, tools, infrastructure
- Home and building controls



COMPUTER

- Notebooks, servers, desktops, embedded, edge computing, portable computers, tablets, super computers, DRAM
- Peripherals

The Key Specifications

Part Number	$I_{F(AV)}$ (A)	V_{RRM} (V)	I_{FSM} (A)	V_F at I_F and T_J			T_J Max. (°C)	Package
				V_F (V)	I_F (A)	T_J (°C)		
SE20ND	2	200	32	0.86	2	125	175	DFN3820A
SE20NG	2	400	32	0.86	2	125	175	DFN3820A
SE20NJ	2	600	32	0.86	2	125	175	DFN3820A
SE30ND	3	200	40	0.86	3	125	175	DFN3820A
SE30NG	3	400	40	0.86	3	125	175	DFN3820A
SE30NJ	3	600	40	0.86	3	125	175	DFN3820A
SE40ND	4	200	60	0.86	4	125	175	DFN3820A
SE40NG	4	400	60	0.86	4	125	175	DFN3820A
SE40NJ	4	600	60	0.86	4	125	175	DFN3820A

Vishay Intertechnology introduces three new series of Automotive Grade surface-mount standard rectifiers that are the industry's first devices in the Power DFN Series DFN3820A package with wettable flanks. Providing space-saving, high efficiency solutions, the 2 A SE20Nx, 3 A SE30Nx, and 4 A SE40Nx are each available with reverse voltages of 200 V, 400 V, and 600 V.

- The first package in Vishay's new Power DFN family, the DFN3820A's compact footprint and low profile allow the SE20Nx, SE30Nx, and SE40Nx to make more efficient use of PCB space
- The devices' optimized copper mass design and advanced die placement technology allow for superior thermal performance that enables operation at higher current ratings
- Compared to devices in the SMP (DO-220AA) package with the same footprint, the SE20Nx, SE30Nx, and SE40Nx offer a 12 % lower profile and double the current rating
- The rectifiers offer equivalent or higher current ratings to larger devices in the conventional SMB (DO-214AA) and SMC (DO-214AB) packages, as well as the eSMP® series SlimSMA (DO-221AC), SlimSMAW (DO-221AD), SMPA (DO-221BC), and SMPC (TO-2778)

